
OpenTelemetry C++

Release 1.4.1

OpenTelemetry authors

Jun 20, 2022

OPENTELEMETRY C++ API

1	OpenTelemetry C++ API	1
2	OpenTelemetry C++ SDK	5
3	Reference documentation	11
4	Performance Tests - Benchmarks	95
5	Getting help	97
	Index	99

OPENTELEMETRY C++ API

1.1 Overview

The OpenTelemetry C++ API enables developers to instrument their applications and libraries in order to make them ready to create and emit telemetry data. The OpenTelemetry C++ API exclusively focuses on instrumentation and does not address concerns like exporting, sampling, and aggregating telemetry data. Those concerns are addressed by the OpenTelemetry C++ SDK. This architecture enables developers to instrument applications and libraries with the OpenTelemetry C++ API while being completely agnostic of how telemetry data is exported and processed.

1.1.1 Library design

The OpenTelemetry C++ API is provided as a header-only library and supports all recent versions of the C++ standard, down to C++11.

A single application might dynamically or statically link to different libraries that were compiled with different compilers, while several of the linked libraries are instrumented with OpenTelemetry. OpenTelemetry C++ supports those scenarios by providing a stable ABI. This is achieved by a careful API design, and most notably by providing ABI stable versions of classes from the standard library. All those classes are provided in the `opentelemetry::nostd` namespace.

1.2 Getting started

1.2.1 Tracing

When instrumenting libraries and applications, the most simple approach requires three steps.

Obtain a tracer

```
auto provider = opentelemetry::trace::Provider::GetTracerProvider();  
auto tracer = provider->GetTracer("foo_library", "1.0.0");
```

The `TracerProvider` acquired in the first step is a singleton object that is usually provided by the OpenTelemetry C++ SDK. It is used to provide specific implementations for API interfaces. In case no SDK is used, the API provides a default no-op implementation of a `TracerProvider`.

The `Tracer` acquired in the second step is needed to create and start `Spans`.

Start a span

```
auto span = tracer->StartSpan("HandleRequest");
```

This creates a span, sets its name to "HandleRequest", and sets its start time to the current time. Refer to the API documentation for other operations that are available to enrich spans with additional data.

Mark a span as active

```
auto scope = tracer->WithActiveSpan(span);
```

This marks a span as active and returns a Scope object. The scope object controls how long a span is active. The span remains active for the lifetime of the scope object.

The concept of an active span is important, as any span that is created without explicitly specifying a parent is parented to the currently active span. A span without a parent is called root span.

Create nested Spans

```
auto outer_span = tracer->StartSpan("Outer operation");
auto outer_scope = tracer->WithActiveSpan(outer_span);
{
    auto inner_span = tracer->StartSpan("Inner operation");
    auto inner_scope = tracer->WithActiveSpan(inner_span);
    // ... perform inner operation
    inner_span->End();
}
// ... perform outer operation
outer_span->End();
```

Spans can be nested, and have a parent-child relationship with other spans. When a given span is active, the newly created span inherits the active span's trace ID, and other context attributes.

Context Propagation

```
// set global propagator
opentelemetry::context::propagation::GlobalTextMapPropagator::SetGlobalPropagator(
    nostd::shared_ptr<opentelemetry::context::propagation::TextMapPropagator>(
        new opentelemetry::trace::propagation::HttpTraceContext()));

// get global propagator
HttpTextMapCarrier<opentelemetry::ext::http::client::Headers> carrier;
auto propagator =
    opentelemetry::context::propagation::GlobalTextMapPropagator::GetGlobalPropagator();

//inject context to headers
auto current_ctx = opentelemetry::context::RuntimeContext::GetCurrent();
propagator->Inject(carrier, current_ctx);

//Extract headers to context
```

(continues on next page)

(continued from previous page)

```
auto current_ctx = opentelemetry::context::RuntimeContext::GetCurrent();  
auto new_context = propagator->Extract(carrier, current_ctx);  
auto remote_span = opentelemetry::trace::propagation::GetSpan(new_context);
```

Context contains the meta-data of the currently active Span including Span Id, Trace Id, and flags. Context Propagation is an important mechanism in distributed tracing to transfer this Context across service boundary often through HTTP headers. OpenTelemetry provides a text-based approach to propagate context to remote services using the W3C Trace Context HTTP headers.

OPENTELEMETRY C++ SDK

2.1 Getting started

OpenTelemetry C++ SDK provides the reference implementation of OpenTelemetry C++ API, and also provides implementation for Processor, Sampler, and core Exporters as per the specification.

2.2 Exporter

An exporter is responsible for sending the telemetry data to a particular backend. OpenTelemetry offers six tracing exporters out of the box:

- In-Memory Exporter: keeps the data in memory, useful for debugging.
- Jaeger Exporter: prepares and sends the collected telemetry data to a Jaeger backend via UDP and HTTP.
- Zipkin Exporter: prepares and sends the collected telemetry data to a Zipkin backend via the Zipkin APIs.
- Logging Exporter: saves the telemetry data into log streams.
- OpenTelemetry(otlp) Exporter: sends the data to the OpenTelemetry Collector using protobuf/gRPC or protobuf/HTTP.
- ETW Exporter: sends the telemetry data to Event Tracing for Windows (ETW).

```
//namespace alias used in sample code here.
namespace sdktrace = opentelemetry::sdk::trace;

// logging exporter
auto ostream_exporter =
    std::unique_ptr<sdktrace::SpanExporter>(new
    ↪opentelemetry::exporter::trace::OStreamSpanExporter);

// memory exporter
auto memory_exporter =
    std::unique_ptr<sdktrace::SpanExporter>(new
    ↪opentelemetry::exporter::memory::InMemorySpanExporter);

// zipkin exporter
opentelemetry::exporter::zipkin::ZipkinExporterOptions opts;
opts.endpoint = "http://localhost:9411/api/v2/spans" ; // or export OTEL_EXPORTER_ZIPKIN_
    ↪ENDPOINT="..."
opts.service_name = "default_service" ;
```

(continues on next page)

(continued from previous page)

```

auto zipkin_exporter =
    std::unique_ptr<sdktrace::SpanExporter>(new
↳ opentelemetry::exporter::zipkin::ZipkinExporter(opts));

// Jaeger UDP exporter
opentelemetry::exporter::jaeger::JaegerExporterOptions opts;
opts.endpoint = "localhost";
opts.server_port = 6831;
auto jaeger_udp_exporter =
    std::unique_ptr<sdktrace::SpanExporter>(new
↳ opentelemetry::exporter::jaeger::JaegerExporter(opts));

// Jaeger HTTP exporter
opentelemetry::exporter::jaeger::JaegerExporterOptions opts;
opts.transport_format = opentelemetry::exporter::jaeger::TransportFormat::kThriftHttp;
opts.endpoint = "localhost";
opts.server_port = 14268;
opts.headers = {}; // optional headers
auto jaeger_http_exporter =
    std::unique_ptr<sdktrace::SpanExporter>(new
↳ opentelemetry::exporter::jaeger::JaegerExporter(opts));

// otlp grpc exporter
opentelemetry::exporter::otlp::OtlpGrpcExporterOptions opts;
opts.endpoint = "localhost:4317";
opts.use_ssl_credentials = true;
opts.ssl_credentials_cacert_as_string = "ssl-certificate";
auto otlp_grpc_exporter =
    std::unique_ptr<sdktrace::SpanExporter>(new
↳ opentelemetry::exporter::otlp::OtlpGrpcExporter(opts));

// otlp http exporter
opentelemetry::exporter::otlp::OtlpHttpExporterOptions opts;
opts.url = "http://localhost:4318/v1/traces";
auto otlp_http_exporter =
    std::unique_ptr<sdktrace::SpanExporter>(new
↳ opentelemetry::exporter::otlp::OtlpHttpExporter(opts));

```

2.3 Span Processor

Span Processor is initialised with an Exporter. Different Span Processors are offered by OpenTelemetry C++ SDK:

- SimpleSpanProcessor: immediately forwards ended spans to the exporter.
- BatchSpanProcessor: batches the ended spans and send them to exporter in bulk.
- MultiSpanProcessor: Allows multiple span processors to be active and configured at the same time.

```

// simple processor
auto simple_processor = std::unique_ptr<sdktrace::SpanProcessor>(

```

(continues on next page)

(continued from previous page)

```

    new sdktrace::SimpleSpanProcessor(std::move(ostream_exporter)));

// batch processor
sdktrace::BatchSpanProcessorOptions options{};
auto batch_processor = std::unique_ptr<sdktrace::SpanProcessor>(
    new sdktrace::BatchSpanProcessor(std::move(memory_exporter), options));

// multi-processor
std::vector<std::unique_ptr<SpanProcessor>>
    processors{std::move(simple_processor), std::move(batch_processor)};
auto multi_processor = std::unique_ptr<sdktrace::SpanProcessor>(
    new sdktrace::MultiSpanProcessor(std::move(processors)));

```

2.4 Resource

A Resource is an immutable representation of the entity producing telemetry as key-value pair. The OpenTelemetry C++ SDK allow for creation of Resources and for associating them with telemetry.

```

auto resource_attributes = opentelemetry::sdk::resource::ResourceAttributes
{
    {"service.name", "shoppingcart"},
    {"service.instance.id", "instance-12"}
};
auto resource = opentelemetry::sdk::resource::Resource::Create(resource_attributes);
auto received_attributes = resource.GetAttributes();
// received_attributes contains
//   - service.name = shoppingcart
//   - service.instance.id = instance-12
//   - telemetry.sdk.name = opentelemetry
//   - telemetry.sdk.language = cpp
//   - telemetry.sdk.version = <current sdk version>

```

It is possible to define the custom resource detectors by inhering from *opentelemetry::sdk::Resource::ResourceDetector* class.

2.5 Sampler

Sampling is mechanism to control/reducing the number of samples of traces collected and sent to the backend. OpenTelemetry C++ SDK offers four samplers out of the box:

- AlwaysOnSampler which samples every trace regardless of upstream sampling decisions.
- AlwaysOffSampler which doesn't sample any trace, regardless of upstream sampling decisions.
- ParentBased which uses the parent span to make sampling decisions, if present.
- TraceIdRatioBased which samples a configurable percentage of traces.

```

//AlwaysOnSampler
auto always_on_sampler = std::unique_ptr<sdktrace::AlwaysOnSampler>

```

(continues on next page)

(continued from previous page)

```

    (new sdktrace::AlwaysOnSampler);

//AlwaysOffSampler
auto always_off_sampler = std::unique_ptr<sdktrace::AlwaysOffSampler>
    (new sdktrace::AlwaysOffSampler);

//ParentBasedSampler
auto parent_based_sampler = std::unique_ptr<sdktrace::ParentBasedSampler>
    (new sdktrace::ParentBasedSampler);

//TraceIdRatioBasedSampler - Sample 50% generated spans
double ratio = 0.5;
auto always_off_sampler = std::unique_ptr<sdktrace::TraceIdRatioBasedSampler>
    (new sdktrace::TraceIdRatioBasedSampler(ratio));

```

2.6 TracerContext

SDK configuration are shared between *TracerProvider* and all its *Tracer* instances through *TracerContext*.

```

auto tracer_context = std::make_shared<sdktrace::TracerContext>
    (std::move(multi_processor), resource, std::move(always_on_sampler));

```

2.7 TracerProvider

TracerProvider instance holds the SDK configurations (Span Processors, Samplers, Resource). There is single global *TracerProvider* instance for an application, and it is created at the start of application. There are two different mechanisms to create *TraceProvider* instance

- Using constructor which takes already created *TracerContext* shared object as parameter.
- Using constructor which takes SDK configurations as parameter.

```

// Created using `TracerContext` instance
auto tracer_provider = nostd::shared_ptr<sdktrace::TracerProvider>
    (new sdktrace::TracerProvider(tracer_context));

// Create using SDK configurations as parameter
auto tracer_provider = nostd::shared_ptr<sdktrace::TracerProvider>
    (std::move(simple_processor), resource, std::move(always_on_sampler));

// set the global tracer TracerProvider
opentelemetry::trace::Provider::SetTracerProvider(tracer_provider);

```

2.8 Logging and Error Handling

OpenTelemetry C++ SDK provides mechanism for application owner to add customer log and error handler. The default log handler is redirected to standard output (using `std::cout`).

The logging macro supports logging using C++ stream format, and key-value pair. The log handler is meant to capture errors and warnings arising from SDK, not supposed to be used for the application errors. The different log levels are supported - Error, Warn, Info and Debug. The default log level is Warn (to dump both Error and Warn) and it can be changed at compile time.

```
OTEL_INTERNAL_LOG_ERROR(" Connection failed. Error string " << error_str << " Error Num:
↳ " << errorno);
opentelemetry::sdk::common::AttributeMap error_attributes = {
    {"url", url}, {"content-length", len}, {"content-type", type}};
OTEL_INTERNAL_LOG_ERROR(" Connection failed." , error_attributes);
opentelemetry::sdk::common::AttributeMap http_attributes = {
    {"url", url}, {"content-length", len}, {"content-type", type}};
OTEL_INTERNAL_LOG_DEBUG(" Connection Established Successfully. Headers:", http_
↳ attributes);
```

The custom log handler can be defined by inheriting from `opentelemetry::sdk::common::internal_log::LogHandler` class.

```
class CustomLogHandler : public opentelemetry::sdk::common::internal_log::LogHandler
{
    void Handle(opentelemetry::sdk::common::internal_log::LogLevel level,
                const char \*file,
                int line,
                const char \*msg,
                const opentelemetry::sdk::common::AttributeMap &attributes) noexcept
↳ override
    {
        // add implementation here
    }
};
opentelemetry::sdk::common::internal_
↳ log::GlobalLogHandler::SetLogHandler(CustomLogHandler());
opentelemetry::sdk::common::internal_
↳ log::GlobalLogHandler::SetLogLevel(opentelemetry::sdk::common::internal_
↳ log::LogLevel::Debug);
```


REFERENCE DOCUMENTATION

3.1 Full API

3.1.1 Namespaces

Namespace opentelemetry

Contents

- *Namespaces*

Namespaces

- *Namespace opentelemetry::baggage*
- *Namespace opentelemetry::common*
- *Namespace opentelemetry::context*
- *Namespace opentelemetry::sdk*
- *Namespace opentelemetry::trace*

Namespace opentelemetry::baggage

Contents

- *Namespaces*
- *Classes*
- *Functions*
- *Variables*

Namespaces

- *Namespace `opentelemetry::baggage::propagation`*

Classes

- *Class `Baggage`*

Functions

- *Function `opentelemetry::baggage::GetBaggage`*
- *Function `opentelemetry::baggage::SetBaggage`*

Variables

- *Variable `opentelemetry::baggage::kBaggageHeader`*

Namespace `opentelemetry::baggage::propagation`

Contents

- *Classes*

Classes

- *Class `BaggagePropagator`*

Namespace `opentelemetry::common`

Contents

- *Classes*
- *Typedefs*

Classes

- *Class `KeyValueIterable`*
- *Class `SteadyTimestamp`*
- *Class `SystemTimestamp`*

Typedefs

- *Typedef `opentelemetry::common::AttributeValue`*

Namespace `opentelemetry::context`

Contents

- *Namespaces*
- *Classes*
- *Functions*
- *Typedefs*

Namespaces

- *Namespace `opentelemetry::context::propagation`*

Classes

- *Class `Context`*
- *Class `RuntimeContext`*
- *Class `RuntimeContextStorage`*
- *Class `ThreadLocalContextStorage`*
- *Class `Token`*

Functions

- *Function `opentelemetry::context::GetDefaultStorage`*

Typedefs

- *Typedef `opentelemetry::context::ContextValue`*

Namespace `opentelemetry::context::propagation`

Contents

- *Classes*

Classes

- *Class `CompositePropagator`*
- *Class `GlobalTextMapPropagator`*
- *Class `NoOpPropagator`*
- *Class `TextMapCarrier`*
- *Class `TextMapPropagator`*

Namespace `opentelemetry::sdk`

Contents

- *Namespaces*

Namespaces

- *Namespace `opentelemetry::sdk::instrumentationlibrary`*
- *Namespace `opentelemetry::sdk::resource`*
- *Namespace `opentelemetry::sdk::trace`*

Namespace `opentelemetry::sdk::instrumentationlibrary`

Contents

- *Classes*

Classes

- *Class InstrumentationLibrary*

Namespace opentelemetry::sdk::resource

Contents

- *Classes*
- *Functions*
- *Typedefs*
- *Variables*

Classes

- *Class OTELResourceDetector*
- *Class Resource*
- *Class ResourceDetector*

Functions

- *Function opentelemetry::sdk::resource::attr*

Typedefs

- *Typedef opentelemetry::sdk::resource::ResourceAttributes*

Variables

- *Variable opentelemetry::sdk::resource::attribute_ids*

Namespace opentelemetry::sdk::trace

Contents

- *Namespaces*
- *Classes*
- *Enums*

Namespaces

- *Namespace `opentelemetry::sdk::trace::@44`*

Classes

- *Struct `BatchSpanProcessorOptions`*
- *Struct `MultiSpanProcessor::ProcessorNode`*
- *Struct `MultiSpanProcessorOptions`*
- *Struct `SamplingResult`*
- *Class `AlwaysOffSampler`*
- *Class `AlwaysOnSampler`*
- *Class `BatchSpanProcessor`*
- *Class `IdGenerator`*
- *Class `MultiRecordable`*
- *Class `MultiSpanProcessor`*
- *Class `ParentBasedSampler`*
- *Class `RandomIdGenerator`*
- *Class `Recordable`*
- *Class `Sampler`*
- *Class `SimpleSpanProcessor`*
- *Class `SpanData`*
- *Class `SpanDataEvent`*
- *Class `SpanDataLink`*
- *Class `SpanExporter`*
- *Class `SpanProcessor`*
- *Class `TraceIdRatioBasedSampler`*
- *Class `Tracer`*
- *Class `TracerContext`*
- *Class `TracerProvider`*

Enums

- *Enum Decision*

Namespace opentelemetry::sdk::trace::@44

Namespace opentelemetry::trace

Contents

- *Namespaces*
- *Classes*
- *Enums*
- *Functions*
- *Variables*

Namespaces

- *Namespace opentelemetry::trace::propagation*

Classes

- *Struct EndSpanOptions*
- *Struct StartSpanOptions*
- *Class DefaultSpan*
- *Class NoopSpan*
- *Class NoopTracer*
- *Class NoopTracerProvider*
- *Class NullSpanContext*
- *Class Provider*
- *Class Scope*
- *Class Span*
- *Class SpanContext*
- *Class SpanContextKeyValueIterable*
- *Class SpanId*
- *Class TraceFlags*
- *Class TraceId*
- *Class Tracer*
- *Class TracerProvider*

- *Class `TraceState`*

Enums

- *Enum `CanonicalCode`*
- *Enum `SpanKind`*
- *Enum `StatusCode`*

Functions

- *Function `opentelemetry::trace::attr`*
- *Function `opentelemetry::trace::GetSpan`*
- *Function `opentelemetry::trace::SetSpan`*

Variables

- *Variable `opentelemetry::trace::attribute_id`*
- *Variable `opentelemetry::trace::attribute_ids`*
- *Variable `opentelemetry::trace::attribute_key`*
- *Variable `opentelemetry::trace::kSpanKey`*

Namespace `opentelemetry::trace::propagation`

Contents

- *Namespaces*
- *Classes*
- *Variables*

Namespaces

- *Namespace `opentelemetry::trace::propagation::detail`*

Classes

- *Class B3Propagator*
- *Class B3PropagatorExtractor*
- *Class B3PropagatorMultiHeader*
- *Class HttpTraceContext*
- *Class JaegerPropagator*

Variables

- *Variable opentelemetry::trace::propagation::kB3CombinedHeader*
- *Variable opentelemetry::trace::propagation::kB3SampledHeader*
- *Variable opentelemetry::trace::propagation::kB3SpanIdHeader*
- *Variable opentelemetry::trace::propagation::kB3TraceIdHeader*
- *Variable opentelemetry::trace::propagation::kJaegerTraceHeader*
- *Variable opentelemetry::trace::propagation::kSpanIdHexStrLength*
- *Variable opentelemetry::trace::propagation::kSpanIdSize*
- *Variable opentelemetry::trace::propagation::kTraceFlagsSize*
- *Variable opentelemetry::trace::propagation::kTraceIdHexStrLength*
- *Variable opentelemetry::trace::propagation::kTraceIdSize*
- *Variable opentelemetry::trace::propagation::kTraceParent*
- *Variable opentelemetry::trace::propagation::kTraceParentSize*
- *Variable opentelemetry::trace::propagation::kTraceState*
- *Variable opentelemetry::trace::propagation::kVersionSize*

Namespace opentelemetry::trace::propagation::detail

Contents

- *Functions*
- *Variables*

Functions

- Function `opentelemetry::trace::propagation::detail::HexToBinary`
- Function `opentelemetry::trace::propagation::detail::HexToInt`
- Function `opentelemetry::trace::propagation::detail::IsValidHex`
- Function `opentelemetry::trace::propagation::detail::SplitString`

Variables

- Variable `opentelemetry::trace::propagation::detail::kHexDigits`

3.1.2 Classes and Structs

Struct `BatchSpanProcessorOptions`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_batch_span_processor.h`

Struct Documentation

struct **BatchSpanProcessorOptions**

Struct to hold batch *SpanProcessor* options.

Public Members

size_t **max_queue_size** = 2048

The maximum buffer/queue size. After the size is reached, spans are dropped.

std::chrono::milliseconds **schedule_delay_millis** = std::chrono::milliseconds(5000)

size_t **max_export_batch_size** = 512

The maximum batch size of every export. It must be smaller or equal to `max_queue_size`.

Struct `MultiSpanProcessor::ProcessorNode`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_multi_span_processor.h`

Nested Relationships

This struct is a nested type of *Class MultiSpanProcessor*.

Struct Documentation

struct **ProcessorNode**

Public Functions

```
inline ProcessorNode(std::unique_ptr<SpanProcessor> &&value, ProcessorNode *prev = nullptr,  
                     ProcessorNode *next = nullptr)
```

Public Members

std::unique_ptr<*SpanProcessor*> **value_**

ProcessorNode ***next_**

ProcessorNode ***prev_**

Struct MultiSpanProcessorOptions

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_multi_span_processor.h

Struct Documentation

struct **MultiSpanProcessorOptions**

Instantiation options.

Struct SamplingResult

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_sampler.h

Struct Documentation

struct **SamplingResult**

The output of ShouldSample. It contains a sampling Decision and a set of Span Attributes.

Public Members

Decision **decision**

std::unique_ptr<const std::map<std::string, opentelemetry::common::AttributeValue>> **attributes**

nostd::shared_ptr<opentelemetry::trace::TraceState> **trace_state**

Struct EndSpanOptions

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span_metadata.h

Struct Documentation

struct **EndSpanOptions**

EndSpanOptions provides options to set properties of a *Span* when it is ended.

Public Members

common::SteadyTimestamp **end_steady_time**

Struct StartSpanOptions

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span_startoptions.h

Struct Documentation

struct **StartSpanOptions**

StartSpanOptions provides options to set properties of a *Span* at the time of its creation

Public Members

common::SystemTimestamp **start_system_time**

common::SteadyTimestamp **start_steady_time**

nostd::variant<SpanContext, opentelemetry::context::Context> **parent** = SpanContext::GetInvalid()

SpanKind **kind** = SpanKind::kInternal

Class Baggage

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_baggage_baggage.h

Class Documentation

class **Baggage**

Public Functions

inline **Baggage**() noexcept

inline **Baggage**(size_t size) noexcept

template<class T>

inline **Baggage**(const T &keys_and_values) noexcept

inline bool **GetValue**(nostd::string_view key, std::string &value) const noexcept

inline nostd::shared_ptr<Baggage> **Set**(const nostd::string_view &key, const nostd::string_view &value) noexcept

inline bool **GetAllEntries**(nostd::function_ref<bool(nostd::string_view, nostd::string_view)> callback) const noexcept

inline nostd::shared_ptr<Baggage> **Delete**(nostd::string_view key) noexcept

inline std::string **ToHeader**() const noexcept

Public Static Functions

static inline nostd::shared_ptr<*Baggage*> **GetDefault**()

static inline nostd::shared_ptr<*Baggage*> **FromHeader**(nostd::string_view header) noexcept

Public Static Attributes

static constexpr size_t **kMaxKeyValuePairs** = 180

static constexpr size_t **kMaxKeyValueSize** = 4096

static constexpr size_t **kMaxSize** = 8192

static constexpr char **kKeyValueSeparator** = '='

static constexpr char **kMembersSeparator** = ','

static constexpr char **kMetadataSeparator** = ';'

Class BaggagePropagator

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_baggage_propagation_baggage_propagator.h

Inheritance Relationships

Base Type

- public opentelemetry::context::propagation::TextMapPropagator

Class Documentation

class **BaggagePropagator** : public opentelemetry::context::propagation::TextMapPropagator

Public Functions

inline void **Inject**(opentelemetry::context::propagation::TextMapCarrier &carrier, const opentelemetry::context::Context &context) noexcept override

inline context::Context **Extract**(const opentelemetry::context::propagation::TextMapCarrier &carrier, opentelemetry::context::Context &context) noexcept override

inline bool **Fields**(nostd::function_ref<bool(nostd::string_view)> callback) const noexcept override

Class KeyValueIterable

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_common_key_value_iterable.h`

Class Documentation

class **KeyValueIterable**

Supports internal iteration over a collection of key-value pairs.

Public Functions

virtual **~KeyValueIterable**() = default

virtual bool **ForEachKeyValue**(nostd::function_ref<bool(nostd::string_view, common::AttributeValue)> callback) const noexcept = 0

Iterate over key-value pairs

Parameters **callback** – a callback to invoke for each key-value. If the callback returns false, the iteration is aborted.

Returns true if every key-value pair was iterated over

virtual size_t **size**() const noexcept = 0

Returns the number of key-value pairs

Class SteadyTimestamp

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_common_timestamp.h`

Class Documentation

class **SteadyTimestamp**

A timepoint relative to the monotonic clock epoch.

This is used for calculating the duration of an operation.

Public Functions

inline **SteadyTimestamp**() noexcept

Initializes a monotonic timestamp pointing to the start of the epoch.

template<class **Rep**, class **Period**>

inline explicit **SteadyTimestamp**(const std::chrono::duration<*Rep*, *Period*> &time_since_epoch) noexcept

Initializes a monotonic timestamp from a duration.

Parameters **time_since_epoch** – Time elapsed since the beginning of the epoch.

inline **SteadyTimestamp**(const std::chrono::steady_clock::time_point &time_point) noexcept

Initializes a monotonic timestamp based on a point in time.

Parameters *time_point* – A point in time.

inline **operator** std::chrono::steady_clock::time_point() const noexcept

Returns a time point for the time stamp.

Returns A time point corresponding to the time stamp.

inline std::chrono::nanoseconds **time_since_epoch**() const noexcept

Returns the nanoseconds since the beginning of the epoch.

Returns Elapsed nanoseconds since the beginning of the epoch for this timestamp.

inline bool **operator==**(const *SteadyTimestamp* &other) const noexcept

Compare two steady time stamps.

Returns true if the two time stamps are equal.

inline bool **operator!=**(const *SteadyTimestamp* &other) const noexcept

Compare two steady time stamps for inequality.

Returns true if the two time stamps are not equal.

Class SystemTimestamp

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_common_timestamp.h`

Class Documentation

class **SystemTimestamp**

A timepoint relative to the system clock epoch.

This is used for marking the beginning and end of an operation.

Public Functions

inline **SystemTimestamp**() noexcept

Initializes a system timestamp pointing to the start of the epoch.

template<class **Rep**, class **Period**>

inline explicit **SystemTimestamp**(const std::chrono::duration<*Rep*, *Period*> &time_since_epoch) noexcept

Initializes a system timestamp from a duration.

Parameters *time_since_epoch* – Time elapsed since the beginning of the epoch.

inline **SystemTimestamp**(const std::chrono::system_clock::time_point &time_point) noexcept

Initializes a system timestamp based on a point in time.

Parameters *time_point* – A point in time.

inline **operator** `std::chrono::system_clock::time_point()` const noexcept

Returns a time point for the time stamp.

Returns A time point corresponding to the time stamp.

inline `std::chrono::nanoseconds time_since_epoch()` const noexcept

Returns the nanoseconds since the beginning of the epoch.

Returns Elapsed nanoseconds since the beginning of the epoch for this timestamp.

inline bool **operator**==(const *SystemTimestamp* &other) const noexcept

Compare two steady time stamps.

Returns true if the two time stamps are equal.

inline bool **operator**!=(const *SystemTimestamp* &other) const noexcept

Compare two steady time stamps for inequality.

Returns true if the two time stamps are not equal.

Class Context

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_context.h`

Class Documentation

class **Context**

Public Functions

Context() = default

template<class T>

inline **Context**(const T &keys_and_values) noexcept

inline **Context**(nostd::string_view key, *ContextValue* value) noexcept

template<class T>

inline *Context* **SetValues**(T &values) noexcept

inline *Context* **SetValue**(nostd::string_view key, *ContextValue* value) noexcept

inline *context::ContextValue* **GetValue**(const nostd::string_view key) const noexcept

inline bool **HasKey**(const nostd::string_view key) const noexcept

inline bool **operator**==(const *Context* &other) const noexcept

Class CompositePropagator

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_propagation_composite_propagator.h`

Inheritance Relationships

Base Type

- `public opentelemetry::context::propagation::TextMapPropagator`

Class Documentation

class **CompositePropagator** : public `opentelemetry::context::propagation::TextMapPropagator`

Public Functions

inline **CompositePropagator**(`std::vector<std::unique_ptr<TextMapPropagator>>` propagators)

inline void **Inject**(`TextMapCarrier` &carrier, const `context::Context` &context) noexcept override

Run each of the configured propagators with the given context and carrier. Propagators are run in the order they are configured, so if multiple propagators write the same carrier key, the propagator later in the list will “win”.

Parameters

- carrier** – Carrier into which context will be injected
- context** – Context to inject

inline `context::Context` **Extract**(const `TextMapCarrier` &carrier, `context::Context` &context) noexcept override

Run each of the configured propagators with the given context and carrier. Propagators are run in the order they are configured, so if multiple propagators write the same context key, the propagator later in the list will “win”.

Parameters

- carrier** – Carrier from which to extract context
- context** – Context to add values to

inline bool **Fields**(`nostd::function_ref<bool(nostd::string_view)>` callback) const noexcept override

Invoke callback with fields set to carrier by `inject` method for all the configured propagators Returns true if all invocation return true

Class GlobalTextMapPropagator

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_propagation_global_propagator.h

Class Documentation

class **GlobalTextMapPropagator**

Public Static Functions

static inline nostd::shared_ptr<*TextMapPropagator*> **GetGlobalPropagator**() noexcept

static inline void **SetGlobalPropagator**(nostd::shared_ptr<*TextMapPropagator*> prop) noexcept

Class NoOpPropagator

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_propagation_noop_propagator.h

Inheritance Relationships

Base Type

- public opentelemetry::context::propagation::TextMapPropagator

Class Documentation

class **NoOpPropagator** : public opentelemetry::context::propagation::*TextMapPropagator*
No-op implementation TextMapPropagator

Public Functions

inline *context*::Context **Extract**(const *TextMapCarrier*&, *context*::Context &context) noexcept override
Noop extract function does nothing and returns the input context

inline void **Inject**(*TextMapCarrier*&, const *context*::Context &context) noexcept override
Noop inject function does nothing

inline bool **Fields**(nostd::function_ref<bool(nostd::string_view)> callback) const noexcept override

Class TextMapCarrier

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_propagation_text_map_propagator.h`

Class Documentation

class **TextMapCarrier**

Public Functions

virtual `nostd::string_view` **Get**(`nostd::string_view` key) const noexcept = 0

virtual void **Set**(`nostd::string_view` key, `nostd::string_view` value) noexcept = 0

inline virtual bool **Keys**(`nostd::function_ref<bool(nostd::string_view)>` callback) const noexcept

virtual `~TextMapCarrier()` = default

Class TextMapPropagator

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_propagation_text_map_propagator.h`

Inheritance Relationships

Derived Types

- `public opentelemetry::baggage::propagation::BaggagePropagator` (*Class BaggagePropagator*)
- `public opentelemetry::context::propagation::CompositePropagator` (*Class CompositePropagator*)
- `public opentelemetry::context::propagation::NoOpPropagator` (*Class NoOpPropagator*)
- `public opentelemetry::trace::propagation::B3PropagatorExtractor` (*Class B3PropagatorExtractor*)
- `public opentelemetry::trace::propagation::HttpTraceContext` (*Class HttpTraceContext*)
- `public opentelemetry::trace::propagation::JaegerPropagator` (*Class JaegerPropagator*)

Class Documentation

class **TextMapPropagator**

Subclassed by `opentelemetry::baggage::propagation::BaggagePropagator`, `opentelemetry::context::propagation::CompositePropagator`, `opentelemetry::context::propagation::NoOpPropagator`, `opentelemetry::trace::propagation::B3PropagatorExtractor`, `opentelemetry::trace::propagation::HttpTraceContext`, `opentelemetry::trace::propagation::JaegerPropagator`

Public Functions

```
virtual context::Context Extract(const TextMapCarrier &carrier, context::Context &context) noexcept = 0

virtual void Inject(TextMapCarrier &carrier, const context::Context &context) noexcept = 0

virtual bool Fields(nostd::function_ref<bool(nostd::string_view)> callback) const noexcept = 0

virtual ~TextMapPropagator() = default
```

Class RuntimeContext

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_runtime_context.h`

Class Documentation

class **RuntimeContext**

Public Static Functions

```
static inline Context GetCurrent() noexcept

static inline nostd::unique_ptr<Token> Attach(const Context &context) noexcept

static inline bool Detach(Token &token) noexcept

static inline Context SetValue(nostd::string_view key, const ContextValue &value, Context *context =
    nullptr) noexcept

static inline ContextValue GetValue(nostd::string_view key, Context *context = nullptr) noexcept

static inline void SetRuntimeContextStorage(nostd::shared_ptr<RuntimeContextStorage> storage)
    noexcept
```

Provide a custom runtime context storage.

This provides a possibility to override the default thread-local runtime context storage. This has to be set before any spans are created by the application, otherwise the behavior is undefined.

Parameters `storage` – a custom runtime context storage

```
static inline nostd::shared_ptr<const RuntimeContextStorage> GetConstRuntimeContextStorage()
    noexcept
```

Provide a pointer to const runtime context storage.

The returned pointer can only be used for extending the lifetime of the runtime context storage.

Class RuntimeContextStorage

- Defined in file `_home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_runtime_context.h`

Inheritance Relationships

Derived Type

- `public opentelemetry::context::ThreadLocalContextStorage` (*Class ThreadLocalContextStorage*)

Class Documentation

class **RuntimeContextStorage**

RuntimeContextStorage is used by RuntimeContext to store Context frames.

Custom context management strategies can be implemented by deriving from this class and passing an initialized *RuntimeContextStorage* object to `RuntimeContext::SetRuntimeContextStorage`.

Subclassed by *opentelemetry::context::ThreadLocalContextStorage*

Public Functions

virtual *Context* **GetCurrent**() noexcept = 0

Return the current context.

Returns the current context

virtual `nstd::unique_ptr<Token>` **Attach**(const *Context* &context) noexcept = 0

Set the current context.

Parameters *the* – new current context

Returns a token for the new current context. This never returns a nullptr.

virtual bool **Detach**(*Token* &token) noexcept = 0

Detach the context related to the given token.

Parameters *token* – a token related to a context

Returns true if the context could be detached

inline virtual **~RuntimeContextStorage**()

Protected Functions

inline nstd::unique_ptr<*Token*> **CreateToken**(const *Context* &context) noexcept

Class ThreadLocalContextStorage

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_runtime_context.h

Inheritance Relationships

Base Type

- public opentelemetry::context::RuntimeContextStorage (*Class RuntimeContextStorage*)

Class Documentation

class **ThreadLocalContextStorage** : public opentelemetry::context::RuntimeContextStorage

Public Functions

ThreadLocalContextStorage() noexcept = default

inline *Context* **GetCurrent**() noexcept override

inline bool **Detach**(*Token* &token) noexcept override

inline nstd::unique_ptr<*Token*> **Attach**(const *Context* &context) noexcept override

Class Token

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_runtime_context.h

Class Documentation

class **Token**

Public Functions

```
inline bool operator==(const Context &other) const noexcept  
inline ~Token()
```

Class InstrumentationLibrary

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_instrumentationlibrary_instrumentation_library.h`

Class Documentation

class **InstrumentationLibrary**

Public Functions

InstrumentationLibrary(const *InstrumentationLibrary*&) = default

```
inline std::size_t HashCode() const noexcept
```

```
inline bool operator==(const InstrumentationLibrary &other) const  
    Compare 2 instrumentation libraries.
```

Parameters **other** – the instrumentation library to compare to.

Returns true if the 2 instrumentation libraries are equal, false otherwise.

```
inline bool equal(const nostd::string_view name, const nostd::string_view version, const nostd::string_view  
    schema_url = "") const
```

Check whether the instrumentation library has given name and version. This could be used to check version equality and avoid heap allocation.

Parameters

- **name** – name of the instrumentation library to compare.
- **version** – version of the instrumentatoin library to compare.
- **schema_url** – schema url of the telemetry emitted by the library.

Returns true if name and version in this instrumentation library are equal with the given name and version.

```
inline const std::string &GetName() const
```

```
inline const std::string &GetVersion() const
```

```
inline const std::string &GetSchemaURL() const
```

Public Static Functions

```
static inline nostd::unique_ptr<InstrumentationLibrary> Create(nostd::string_view name, nostd::string_view
                                                                version = "", nostd::string_view schema_url
                                                                = "")
```

Returns a newly created InstrumentationLibrary with the specified library name and version.

Parameters

- **name** – name of the instrumentation library.
- **version** – version of the instrumentation library.
- **schema_url** – schema url of the telemetry emitted by the library.

Returns the newly created InstrumentationLibrary.

Class OTELResourceDetector

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_resource_resource_detector.h`

Inheritance Relationships

Base Type

- public `opentelemetry::sdk::resource::ResourceDetector` (*Class ResourceDetector*)

Class Documentation

class **OTELResourceDetector** : public `opentelemetry::sdk::resource::ResourceDetector`

OTelResourceDetector to detect the presence of and create a Resource from the OTEL_RESOURCE_ATTRIBUTES environment variable.

Public Functions

virtual *Resource* **Detect**() noexcept override

Class Resource

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_resource_resource.h`

Class Documentation

class **Resource**

Public Functions

Resource(const *Resource*&) = default

const *ResourceAttributes* &**GetAttributes**() const noexcept

const std::string &**GetSchemaURL**() const noexcept

Resource **Merge**(const *Resource* &other) noexcept

Returns a new, merged Resource by merging the current Resource with the other Resource. In case of a collision, current Resource takes precedence.

Parameters **other** – the Resource that will be merged with this.

Returns the newly merged Resource.

Public Static Functions

static *Resource* **Create**(const *ResourceAttributes* &attributes, const std::string &schema_url = std::string{ })

Returns a newly created Resource with the specified attributes. It adds (merge) SDK attributes and OTEL attributes before returning.

Parameters **attributes** – for this resource

Returns the newly created Resource.

static *Resource* &**GetEmpty**()

Returns an Empty resource.

static *Resource* &**GetDefault**()

Returns a Resource that identifies the SDK in use.

Protected Functions

Resource(const *ResourceAttributes* &attributes = *ResourceAttributes*(), const std::string &schema_url = std::string{ }) noexcept

The constructor is protected and only for use internally by the class and inside *ResourceDetector* class. Users should use the Create factory method to obtain a Resource instance.

Class ResourceDetector

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_resource_resource_detector.h`

Inheritance Relationships

Derived Type

- public opentelemetry::sdk::resource::OTELResourceDetector (*Class OTELResourceDetector*)

Class Documentation

class **ResourceDetector**

Interface for a Resource Detector

Subclassed by *opentelemetry::sdk::resource::OTELResourceDetector*

Public Functions

virtual *Resource* **Detect**() = 0

Class AlwaysOffSampler

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_samplers_always_off.h

Inheritance Relationships

Base Type

- public opentelemetry::sdk::trace::Sampler (*Class Sampler*)

Class Documentation

class **AlwaysOffSampler** : public opentelemetry::sdk::trace::*Sampler*

The always off sampler always returns DROP, effectively disabling tracing functionality.

Public Functions

inline virtual *SamplingResult* **ShouldSample**(const opentelemetry::trace::*SpanContext* &parent_context, opentelemetry::trace::*TraceId*, nostd::string_view, opentelemetry::trace::*SpanKind*, const opentelemetry::common::*KeyValueIterable*&, const opentelemetry::trace::*SpanContextKeyValueIterable*&) noexcept override

Returns Returns DROP always

inline virtual nostd::string_view **GetDescription**() const noexcept override

Returns Description MUST be *AlwaysOffSampler*

Class AlwaysOnSampler

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_samplers_always_on.h`

Inheritance Relationships

Base Type

- `public opentelemetry::sdk::trace::Sampler` (*Class Sampler*)

Class Documentation

class **AlwaysOnSampler** : public opentelemetry::sdk::trace::*Sampler*

The always on sampler is a default sampler which always return `Decision::RECORD_AND_SAMPLE`

Public Functions

```
inline virtual SamplingResult ShouldSample(const opentelemetry::trace::SpanContext &parent_context,  
                                             opentelemetry::trace::TraceId, nostd::string_view,  
                                             opentelemetry::trace::SpanKind, const  
                                             opentelemetry::common::KeyValueIterable&, const  
                                             opentelemetry::trace::SpanContextKeyValueIterable&)  
noexcept override
```

Returns Always return `Decision RECORD_AND_SAMPLE`

```
inline virtual nostd::string_view GetDescription() const noexcept override
```

Returns Description MUST be *AlwaysOnSampler*

Class BatchSpanProcessor

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_batch_span_processor.h`

Inheritance Relationships

Base Type

- `public opentelemetry::sdk::trace::SpanProcessor` (*Class SpanProcessor*)

Class Documentation

class **BatchSpanProcessor** : public opentelemetry::sdk::trace::SpanProcessor

This is an implementation of the *SpanProcessor* which creates batches of finished spans and passes the export-friendly span data representations to the configured *SpanExporter*.

Public Functions

BatchSpanProcessor(std::unique_ptr<*SpanExporter*> &&exporter, const *BatchSpanProcessorOptions* &options)

Creates a batch span processor by configuring the specified exporter and other parameters as per the official, language-agnostic opentelemetry specs.

Parameters

- **exporter** – - The backend exporter to pass the ended spans to.
- **options** – - The batch *SpanProcessor* options.

virtual std::unique_ptr<*Recordable*> **MakeRecordable**() noexcept override

Requests a Recordable(Span) from the configured exporter.

Returns A recordable generated by the backend exporter

virtual void **OnStart**(*Recordable* &span, const opentelemetry::trace::SpanContext &parent_context) noexcept override

Called when a span is started.

NOTE: This method is a no-op.

Parameters

- **span** – - The span that just started
- **parent_context** – - The parent context of the span that just started

virtual void **OnEnd**(std::unique_ptr<*Recordable*> &&span) noexcept override

Called when a span ends.

Parameters **span** – - A recordable for a span that just ended

virtual bool **ForceFlush**(std::chrono::microseconds timeout = std::chrono::microseconds::max()) noexcept override

Export all ended spans that have not been exported yet.

NOTE: Timeout functionality not supported yet.

virtual bool **Shutdown**(std::chrono::microseconds timeout = std::chrono::microseconds::max()) noexcept override

Shuts down the processor and does any cleanup required. Completely drains the buffer/queue of all its ended spans and passes them to the exporter. Any subsequent calls to OnStart, OnEnd, ForceFlush or Shutdown will return immediately without doing anything.

NOTE: Timeout functionality not supported yet.

~BatchSpanProcessor()

Class destructor which invokes the *Shutdown()* method. The *Shutdown()* method is supposed to be invoked when the Tracer is shutdown (as per other languages), but the C++ Tracer only takes shared ownership of the processor, and thus doesn't call Shutdown (as the processor might be shared with other Tracers).

Class IdGenerator

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_id_generator.h`

Inheritance Relationships

Derived Type

- `public opentelemetry::sdk::trace::RandomIdGenerator` (*Class RandomIdGenerator*)

Class Documentation

class IdGenerator

IdGenerator provides an interface for generating Trace Id and Span Id

Subclassed by *opentelemetry::sdk::trace::RandomIdGenerator*

Public Functions

virtual `~IdGenerator()` = default

virtual `opentelemetry::trace::SpanId GenerateSpanId()` noexcept = 0

Returns a SpanId represented by opaque 128-bit trace identifier

virtual `opentelemetry::trace::TraceId GenerateTraceId()` noexcept = 0

Returns a TraceId represented by opaque 64-bit trace identifier

Class MultiRecordable

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_multi_recordable.h`

Inheritance Relationships

Base Type

- `public opentelemetry::sdk::trace::Recordable` (*Class Recordable*)

Class Documentation

class **MultiRecordable** : public opentelemetry::sdk::trace::Recordable

Public Functions

```

inline void AddRecordable(const SpanProcessor &processor, std::unique_ptr<Recordable> recordable)
    noexcept

inline const std::unique_ptr<Recordable> &GetRecordable(const SpanProcessor &processor) const
    noexcept

inline std::unique_ptr<Recordable> ReleaseRecordable(const SpanProcessor &processor) noexcept

inline void SetIdentity(const opentelemetry::trace::SpanContext &span_context,
    opentelemetry::trace::SpanId parent_span_id) noexcept override

inline void SetAttribute(nstd::string_view key, const opentelemetry::common::AttributeValue &value)
    noexcept override

inline void AddEvent(nstd::string_view name, opentelemetry::common::SystemTimestamp timestamp, const
    opentelemetry::common::KeyValueIterable &attributes) noexcept override

inline void AddLink(const opentelemetry::trace::SpanContext &span_context, const
    opentelemetry::common::KeyValueIterable &attributes) noexcept override

inline void SetStatus(opentelemetry::trace::StatusCode code, nstd::string_view description) noexcept
    override

inline void SetName(nstd::string_view name) noexcept override

inline void SetSpanKind(opentelemetry::trace::SpanKind span_kind) noexcept override

inline void SetResource(const opentelemetry::sdk::resource::Resource &resource) noexcept override

inline void SetStartTime(opentelemetry::common::SystemTimestamp start_time) noexcept override

inline void SetDuration(std::chrono::nanoseconds duration) noexcept override

inline void SetInstrumentationLibrary(const InstrumentationLibrary &instrumentation_library)
    noexcept override

```

Class MultiSpanProcessor

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_multi_span_processor.h

Nested Relationships

Nested Types

- *Struct `MultiSpanProcessor::ProcessorNode`*

Inheritance Relationships

Base Type

- `public opentelemetry::sdk::trace::SpanProcessor` (*Class `SpanProcessor`*)

Class Documentation

class **MultiSpanProcessor** : public opentelemetry::sdk::trace::SpanProcessor

Span processor allow hooks for span start and end method invocations.

Built-in span processors are responsible for batching and conversion of spans to exportable representation and passing batches to exporters.

Public Functions

inline **MultiSpanProcessor**(std::vector<std::unique_ptr<SpanProcessor>> &&processors)

inline void **AddProcessor**(std::unique_ptr<SpanProcessor> &&processor)

inline virtual std::unique_ptr<Recordable> **MakeRecordable**() noexcept override

Create a span recordable. This requests a new span recordable from the associated exporter.

Note: This method must be callable from multiple threads.

Returns a newly initialized recordable

inline virtual void **OnStart**(Recordable &span, const opentelemetry::trace::SpanContext &parent_context) noexcept override

OnStart is called when a span is started.

Parameters

- **span** – a recordable for a span that was just started
- **parent_context** – The parent context of the span that just started

inline virtual void **OnEnd**(std::unique_ptr<Recordable> &&span) noexcept override

OnEnd is called when a span is ended.

Parameters **span** – a recordable for a span that was ended

inline virtual bool **ForceFlush**(std::chrono::microseconds timeout = (std::chrono::microseconds::max)()) noexcept override

Export all ended spans that have not yet been exported.

Parameters **timeout** – an optional timeout, the default timeout of 0 means that no timeout is applied.

```
inline virtual bool Shutdown(std::chrono::microseconds timeout = (std::chrono::microseconds::max>())
                             noexcept override
```

Shut down the processor and do any cleanup required. Ended spans are exported before shutdown. After the call to Shutdown, subsequent calls to OnStart, OnEnd, ForceFlush or Shutdown will return immediately without doing anything.

Parameters **timeout** – an optional timeout, the default timeout of 0 means that no timeout is applied.

```
inline ~MultiSpanProcessor()
```

Class ParentBasedSampler

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_samplers_parent.h`

Inheritance Relationships

Base Type

- public `opentelemetry::sdk::trace::Sampler` (*Class Sampler*)

Class Documentation

```
class ParentBasedSampler : public opentelemetry::sdk::trace::Sampler
```

The ParentBased sampler is a composite sampler. ParentBased(delegateSampler) either respects the parent span's sampling decision or delegates to delegateSampler for root spans.

Public Functions

```
explicit ParentBasedSampler(std::shared_ptr<Sampler> delegate_sampler) noexcept
```

```
virtual SamplingResult ShouldSample(const opentelemetry::trace::SpanContext &parent_context,
                                     opentelemetry::trace::TraceId trace_id, nostd::string_view name,
                                     opentelemetry::trace::SpanKind span_kind, const
                                     opentelemetry::common::KeyValueIterable &attributes, const
                                     opentelemetry::trace::SpanContextKeyValueIterable &links) noexcept
                                     override
```

The decision either respects the parent span's sampling decision or delegates to delegateSampler for root spans

Returns Returns DROP always

```
virtual nostd::string_view GetDescription() const noexcept override
```

Returns Description MUST be ParentBased{delegate_sampler_.getDescription()}

Class RandomIdGenerator

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_random_id_generator.h`

Inheritance Relationships

Base Type

- `public opentelemetry::sdk::trace::IdGenerator` (*Class IdGenerator*)

Class Documentation

class **RandomIdGenerator** : public opentelemetry::sdk::trace::IdGenerator

Public Functions

opentelemetry::trace::SpanId **GenerateSpanId**() noexcept override

opentelemetry::trace::TraceId **GenerateTraceId**() noexcept override

Class Recordable

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_recordable.h`

Inheritance Relationships

Derived Types

- `public opentelemetry::sdk::trace::MultiRecordable` (*Class MultiRecordable*)
- `public opentelemetry::sdk::trace::SpanData` (*Class SpanData*)

Class Documentation

class **Recordable**

Maintains a representation of a span in a format that can be processed by a recorder.

This class is thread-compatible.

Subclassed by `opentelemetry::sdk::trace::MultiRecordable`, `opentelemetry::sdk::trace::SpanData`

Public Functions

virtual **~Recordable()** = default

virtual void **SetIdentity**(const opentelemetry::trace::SpanContext &span_context,
opentelemetry::trace::SpanId parent_span_id) noexcept = 0

Set the span context and parent span id

Parameters

- **span_context** – the span context to set
- **parent_span_id** – the parent span id to set

virtual void **SetAttribute**(nostd::string_view key, const opentelemetry::common::AttributeValue &value)
noexcept = 0

Set an attribute of a span.

Parameters

- **name** – the name of the attribute
- **value** – the attribute value

virtual void **AddEvent**(nostd::string_view name, opentelemetry::common::SystemTimestamp timestamp, const
opentelemetry::common::KeyValueIterable &attributes) noexcept = 0

Add an event to a span.

Parameters

- **name** – the name of the event
- **timestamp** – the timestamp of the event
- **attributes** – the attributes associated with the event

inline void **AddEvent**(nostd::string_view name)

Add an event to a span with default timestamp and attributes.

Parameters **name** – the name of the event

inline void **AddEvent**(nostd::string_view name, opentelemetry::common::SystemTimestamp timestamp)

Add an event to a span with default (empty) attributes.

Parameters

- **name** – the name of the event
- **timestamp** – the timestamp of the event

virtual void **AddLink**(const opentelemetry::trace::SpanContext &span_context, const
opentelemetry::common::KeyValueIterable &attributes) noexcept = 0

Add a link to a span.

Parameters

- **span_context** – the span context of the linked span
- **attributes** – the attributes associated with the link

inline void **AddLink**(opentelemetry::trace::SpanContext span_context)

Add a link to a span with default (empty) attributes.

Parameters **span_context** – the span context of the linked span

virtual void **SetStatus**(opentelemetry::trace::StatusCode code, nstd::string_view description) noexcept = 0

Set the status of the span.

Parameters

- **code** – the status code
- **description** – a description of the status

virtual void **SetName**(nstd::string_view name) noexcept = 0

Set the name of the span.

Parameters **name** – the name to set

virtual void **SetSpanKind**(opentelemetry::trace::SpanKind span_kind) noexcept = 0

Set the spankind of the span.

Parameters **span_kind** – the spankind to set

virtual void **SetResource**(const opentelemetry::sdk::resource::Resource &resource) noexcept = 0

Set Resource of the span

Parameters **Resource** – the resource to set

virtual void **SetStartTime**(opentelemetry::common::SystemTimestamp start_time) noexcept = 0

Set the start time of the span.

Parameters **start_time** – the start time to set

virtual void **SetDuration**(std::chrono::nanoseconds duration) noexcept = 0

Set the duration of the span.

Parameters **duration** – the duration to set

virtual void **SetInstrumentationLibrary**(const InstrumentationLibrary &instrumentation_library)
noexcept = 0

Set the instrumentation library of the span.

Parameters **instrumentation_library** – the instrumentation library to set

Class Sampler

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_sampler.h

Inheritance Relationships

Derived Types

- public opentelemetry::sdk::trace::AlwaysOffSampler (*Class AlwaysOffSampler*)
- public opentelemetry::sdk::trace::AlwaysOnSampler (*Class AlwaysOnSampler*)
- public opentelemetry::sdk::trace::ParentBasedSampler (*Class ParentBasedSampler*)
- public opentelemetry::sdk::trace::TraceIdRatioBasedSampler (*Class TraceIdRatioBasedSampler*)

Class Documentation

class **Sampler**

The *Sampler* interface allows users to create custom samplers which will return a *SamplingResult* based on information that is typically available just before the Span was created.

Subclassed by *opentelemetry::sdk::trace::AlwaysOffSampler*, *opentelemetry::sdk::trace::AlwaysOnSampler*, *opentelemetry::sdk::trace::ParentBasedSampler*, *opentelemetry::sdk::trace::TraceIdRatioBasedSampler*

Public Functions

virtual **~Sampler()** = default

virtual *SamplingResult* **ShouldSample**(const opentelemetry::trace::SpanContext &parent_context, opentelemetry::trace::TraceId trace_id, nostd::string_view name, opentelemetry::trace::SpanKind span_kind, const opentelemetry::common::KeyValueIterable &attributes, const opentelemetry::trace::SpanContextKeyValueIterable &links) noexcept = 0

Called during Span creation to make a sampling decision.

Since 0.1.0

Parameters

- **parent_context** – a const reference to the SpanContext of a parent Span. An invalid SpanContext if this is a root span.
- **trace_id** – the TraceId for the new Span. This will be identical to that in the parentContext, unless this is a root span.
- **name** – the name of the new Span.
- **spanKind** – the opentelemetry::trace::SpanKind of the Span.
- **attributes** – list of AttributeValue with their keys.
- **links** – Collection of links that will be associated with the Span to be created.

Returns sampling result whether span should be sampled or not.

virtual nostd::string_view **GetDescription()** const noexcept = 0

Returns the sampler name or short description with the configuration. This may be displayed on debug pages or in the logs.

Returns the description of this *Sampler*.

Class SimpleSpanProcessor

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_simple_processor.h

Inheritance Relationships

Base Type

- public opentelemetry::sdk::trace::SpanProcessor (*Class SpanProcessor*)

Class Documentation

class **SimpleSpanProcessor** : public opentelemetry::sdk::trace::SpanProcessor

The simple span processor passes finished recordables to the configured *SpanExporter*, as soon as they are finished.

OnEnd and ForceFlush are no-ops.

All calls to the configured *SpanExporter* are synchronized using a spin-lock on an atomic_flag.

Public Functions

inline explicit **SimpleSpanProcessor**(std::unique_ptr<*SpanExporter*> &&exporter) noexcept

Initialize a simple span processor.

Parameters **exporter** – the exporter used by the span processor

inline virtual std::unique_ptr<*Recordable*> **MakeRecordable**() noexcept override

Create a span recordable. This requests a new span recordable from the associated exporter.

Note: This method must be callable from multiple threads.

Returns a newly initialized recordable

inline virtual void **OnStart**(*Recordable* &span, const opentelemetry::trace::SpanContext &parent_context) noexcept override

OnStart is called when a span is started.

Parameters

- span** – a recordable for a span that was just started
- parent_context** – The parent context of the span that just started

inline virtual void **OnEnd**(std::unique_ptr<*Recordable*> &&span) noexcept override

OnEnd is called when a span is ended.

Parameters **span** – a recordable for a span that was ended

```
inline virtual bool ForceFlush(std::chrono::microseconds timeout = (std::chrono::microseconds::max)())
    noexcept override
```

Export all ended spans that have not yet been exported.

Parameters **timeout** – an optional timeout, the default timeout of 0 means that no timeout is applied.

```
inline virtual bool Shutdown(std::chrono::microseconds timeout = (std::chrono::microseconds::max)())
    noexcept override
```

Shut down the processor and do any cleanup required. Ended spans are exported before shutdown. After the call to Shutdown, subsequent calls to OnStart, OnEnd, ForceFlush or Shutdown will return immediately without doing anything.

Parameters **timeout** – an optional timeout, the default timeout of 0 means that no timeout is applied.

```
inline ~SimpleSpanProcessor()
```

Class SpanData

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_span_data.h`

Inheritance Relationships

Base Type

- public `opentelemetry::sdk::trace::Recordable` (*Class Recordable*)

Class Documentation

class **SpanData** : public `opentelemetry::sdk::trace::Recordable`
SpanData is a representation of all data collected by a span.

Public Functions

```
inline SpanData()
```

```
inline opentelemetry::trace::TraceId GetTraceId() const noexcept
```

Get the trace id for this span

Returns the trace id for this span

```
inline opentelemetry::trace::SpanId GetSpanId() const noexcept
```

Get the span id for this span

Returns the span id for this span

```
inline const opentelemetry::trace::SpanContext &GetSpanContext() const noexcept
```

Get the span context for this span

Returns the span context for this span

```

inline opentelemetry::trace::SpanId GetParentSpanId() const noexcept
    Get the parent span id for this span

    Returns the span id for this span's parent

inline opentelemetry::nostd::string_view GetName() const noexcept
    Get the name for this span

    Returns the name for this span

inline opentelemetry::trace::SpanKind GetSpanKind() const noexcept
    Get the kind of this span

    Returns the kind of this span

inline opentelemetry::trace::StatusCode GetStatus() const noexcept
    Get the status for this span

    Returns the status for this span

inline opentelemetry::nostd::string_view GetDescription() const noexcept
    Get the status description for this span

    Returns the description of the the status of this span

inline const opentelemetry::sdk::resource::Resource &GetResource() const noexcept
    Get the attributes associated with the resource

    Returns the attributes associated with the resource configured for TracerProvider

inline const opentelemetry::sdk::trace::InstrumentationLibrary &GetInstrumentationLibrary() const
                                                                                               noexcept
    Get the attributes associated with the resource

    Returns the attributes associated with the resource configured for TracerProvider

inline opentelemetry::common::SystemTimestamp GetStartTime() const noexcept
    Get the start time for this span

    Returns the start time for this span

inline std::chrono::nanoseconds GetDuration() const noexcept
    Get the duration for this span

    Returns the duration for this span

inline const std::unordered_map<std::string, common::OwnedAttributeValue> &GetAttributes() const
                                                                                               noexcept
    Get the attributes for this span

    Returns the attributes for this span

inline const std::vector<SpanDataEvent> &GetEvents() const noexcept
    Get the events associated with this span

    Returns the events associated with this span

inline const std::vector<SpanDataLink> &GetLinks() const noexcept
    Get the links associated with this span

    Returns the links associated with this span

```

```
inline virtual void SetIdentity(const opentelemetry::trace::SpanContext &span_context,
                                opentelemetry::trace::SpanId parent_span_id) noexcept override
```

Set the span context and parent span id

Parameters

- **span_context** – the span context to set
- **parent_span_id** – the parent span id to set

```
inline virtual void SetAttribute(nostd::string_view key, const opentelemetry::common::AttributeValue
                                   &value) noexcept override
```

Set an attribute of a span.

Parameters

- **name** – the name of the attribute
- **value** – the attribute value

```
inline virtual void AddEvent(nostd::string_view name, opentelemetry::common::SystemTimestamp timestamp
                                =
                                opentelemetry::common::SystemTimestamp(std::chrono::system_clock::now()),
                                const opentelemetry::common::KeyValueIterable &attributes =
                                opentelemetry::common::KeyValueIterableView<std::map<std::string,
                                int>>({})) noexcept override
```

Add an event to a span.

Parameters

- **name** – the name of the event
- **timestamp** – the timestamp of the event
- **attributes** – the attributes associated with the event

```
inline virtual void AddLink(const opentelemetry::trace::SpanContext &span_context, const
                               opentelemetry::common::KeyValueIterable &attributes) noexcept override
```

Add a link to a span.

Parameters

- **span_context** – the span context of the linked span
- **attributes** – the attributes associated with the link

```
inline virtual void SetStatus(opentelemetry::trace::StatusCode code, nostd::string_view description)
                                noexcept override
```

Set the status of the span.

Parameters

- **code** – the status code
- **description** – a description of the status

```
inline virtual void SetName(nostd::string_view name) noexcept override
```

Set the name of the span.

Parameters **name** – the name to set

inline virtual void **SetSpanKind**(opentelemetry::trace::SpanKind span_kind) noexcept override

Set the spankind of the span.

Parameters **span_kind** – the spankind to set

inline virtual void **SetResource**(const opentelemetry::sdk::resource::Resource &resource) noexcept override

Set Resource of the span

Parameters **Resource** – the resource to set

inline virtual void **SetStartTime**(opentelemetry::common::SystemTimestamp start_time) noexcept override

Set the start time of the span.

Parameters **start_time** – the start time to set

inline virtual void **SetDuration**(std::chrono::nanoseconds duration) noexcept override

Set the duration of the span.

Parameters **duration** – the duration to set

inline virtual void **SetInstrumentationLibrary**(const InstrumentationLibrary &instrumentation_library) noexcept override

Set the instrumentation library of the span.

Parameters **instrumentation_library** – the instrumentation library to set

Class SpanDataEvent

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_span_data.h

Class Documentation

class **SpanDataEvent**

Class for storing events in *SpanData*.

Public Functions

inline **SpanDataEvent**(std::string name, opentelemetry::common::SystemTimestamp timestamp, const opentelemetry::common::KeyValueIterable &attributes)

inline std::string **GetName**() const noexcept

Get the name for this event

Returns the name for this event

inline opentelemetry::common::SystemTimestamp **GetTimestamp**() const noexcept

Get the timestamp for this event

Returns the timestamp for this event

inline const std::unordered_map<std::string, common::OwnedAttributeValue> &**GetAttributes**() const noexcept

Get the attributes for this event

Returns the attributes for this event

Class SpanDataLink

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_span_data.h`

Class Documentation

class **SpanDataLink**

Class for storing links in *SpanData*.

Public Functions

inline **SpanDataLink**(opentelemetry::trace::SpanContext span_context, const opentelemetry::common::KeyValueIterable &attributes)

inline const std::unordered_map<std::string, common::OwnedAttributeValue> &**GetAttributes**() const noexcept

Get the attributes for this link

Returns the attributes for this link

inline const opentelemetry::trace::SpanContext &**GetSpanContext**() const noexcept

Get the span context for this link

Returns the span context for this link

Class SpanExporter

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_exporter.h`

Class Documentation

class **SpanExporter**

SpanExporter defines the interface that protocol-specific span exporters must implement.

Public Functions

virtual ~**SpanExporter**() = default

virtual std::unique_ptr<Recordable> **MakeRecordable**() noexcept = 0

Create a span recordable. This object will be used to record span data and will subsequently be passed to *SpanExporter::Export*. Vendors can implement custom recordables or use the default *SpanData* recordable provided by the SDK.

Note: This method must be callable from multiple threads.

Returns a newly initialized *Recordable* object

```
virtual sdk::common::ExportResult Export(const  
                                         nostd::span<std::unique_ptr<opentelemetry::sdk::trace::Recordable>>  
                                         &spans) noexcept = 0
```

Exports a batch of span recordables. This method must not be called concurrently for the same exporter instance.

Parameters **spans** – a span of unique pointers to span recordables

```
virtual bool Shutdown(std::chrono::microseconds timeout = std::chrono::microseconds::max()) noexcept = 0
```

Shut down the exporter.

Parameters **timeout** – an optional timeout.

Returns return the status of the operation.

Class SpanProcessor

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_processor.h`

Inheritance Relationships

Derived Types

- `public opentelemetry::sdk::trace::BatchSpanProcessor` (*Class [BatchSpanProcessor](#)*)
- `public opentelemetry::sdk::trace::MultiSpanProcessor` (*Class [MultiSpanProcessor](#)*)
- `public opentelemetry::sdk::trace::SimpleSpanProcessor` (*Class [SimpleSpanProcessor](#)*)

Class Documentation

class **SpanProcessor**

Span processor allow hooks for span start and end method invocations.

Built-in span processors are responsible for batching and conversion of spans to exportable representation and passing batches to exporters.

Subclassed by `opentelemetry::sdk::trace::BatchSpanProcessor`, `opentelemetry::sdk::trace::MultiSpanProcessor`, `opentelemetry::sdk::trace::SimpleSpanProcessor`

Public Functions

```
virtual ~SpanProcessor() = default
```

```
virtual std::unique_ptr<Recordable> MakeRecordable() noexcept = 0
```

Create a span recordable. This requests a new span recordable from the associated exporter.

Note: This method must be callable from multiple threads.

Returns a newly initialized recordable

virtual void **OnStart**(*Recordable* &span, const opentelemetry::trace::SpanContext &parent_context) noexcept = 0

OnStart is called when a span is started.

Parameters

- **span** – a recordable for a span that was just started
- **parent_context** – The parent context of the span that just started

virtual void **OnEnd**(std::unique_ptr<*Recordable*> &&span) noexcept = 0

OnEnd is called when a span is ended.

Parameters **span** – a recordable for a span that was ended

virtual bool **ForceFlush**(std::chrono::microseconds timeout = (std::chrono::microseconds::max)()) noexcept = 0

Export all ended spans that have not yet been exported.

Parameters **timeout** – an optional timeout, the default timeout of 0 means that no timeout is applied.

virtual bool **Shutdown**(std::chrono::microseconds timeout = (std::chrono::microseconds::max)()) noexcept = 0

Shut down the processor and do any cleanup required. Ended spans are exported before shutdown. After the call to Shutdown, subsequent calls to OnStart, OnEnd, ForceFlush or Shutdown will return immediately without doing anything.

Parameters **timeout** – an optional timeout, the default timeout of 0 means that no timeout is applied.

Class TraceIdRatioBasedSampler

- Defined in file __home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_samplers_trace_id_ratio.h

Inheritance Relationships

Base Type

- public opentelemetry::sdk::trace::Sampler (*Class Sampler*)

Class Documentation

class **TraceIdRatioBasedSampler** : public opentelemetry::sdk::trace::Sampler

The TraceIdRatioBased sampler computes and returns a decision based on the provided trace_id and the configured ratio.

Public Functions

explicit **TraceIdRatioBasedSampler**(double ratio)

Parameters **ratio** – a required value, $1.0 \geq \text{ratio} \geq 0.0$. If the given trace_id falls into a given ratio of all possible trace_id values, ShouldSample will return RECORD_AND_SAMPLE.

Throws `invalid_argument` – if ratio is out of bounds [0.0, 1.0]

virtual *SamplingResult* **ShouldSample**(const opentelemetry::trace::SpanContext&, opentelemetry::trace::TraceId trace_id, nostd::string_view, opentelemetry::trace::SpanKind, const opentelemetry::common::KeyValueIterable&, const opentelemetry::trace::SpanContextKeyValueIterable&) noexcept override

Returns Returns either RECORD_AND_SAMPLE or DROP based on current sampler configuration and provided trace_id and ratio. trace_id is used as a pseudorandom value in conjunction with the predefined ratio to determine whether this trace should be sampled

virtual nostd::string_view **GetDescription**() const noexcept override

Returns Description MUST be *TraceIdRatioBasedSampler*{0.000100}

Class Tracer

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_tracer.h`

Inheritance Relationships

Base Types

- public opentelemetry::trace::Tracer (*Class Tracer*)
- public std::enable_shared_from_this< Tracer >

Class Documentation

class **Tracer** : public opentelemetry::trace::Tracer, public std::enable_shared_from_this<Tracer>

Public Functions

explicit **Tracer**(std::shared_ptr<sdk::trace::TracerContext> context, std::unique_ptr<InstrumentationLibrary> instrumentation_library = InstrumentationLibrary::Create("")) noexcept

Construct a new Tracer with the given context pipeline.

nostd::shared_ptr<trace_api::Span> **StartSpan**(nostd::string_view name, const opentelemetry::common::KeyValueIterable &attributes, const trace_api::SpanContextKeyValueIterable &links, const trace_api::StartSpanOptions &options = {}) noexcept override

```

void ForceFlushWithMicroseconds(uint64_t timeout) noexcept override

void CloseWithMicroseconds(uint64_t timeout) noexcept override

inline SpanProcessor &GetProcessor() noexcept
    Returns the configured span processor.

inline IdGenerator &GetIdGenerator() const noexcept
    Returns the configured Id generator

inline const InstrumentationLibrary &GetInstrumentationLibrary() const noexcept
    Returns the associated instrumentation library

inline const opentelemetry::sdk::resource::Resource &GetResource()
    Returns the currently configured resource

inline Sampler &GetSampler()

```

Class TracerContext

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_tracer_context.h`

Class Documentation

class **TracerContext**

A class which stores the TracerProvider context.

This class meets the following design criteria:

- A shared reference between TracerProvider and Tracers instantiated.
- A thread-safe class that allows updating/altering processor/exporter pipelines and sampling config.
- The owner/destroyer of Processors/Exporters. These will remain active until this class is destroyed. I.e. Sampling, Exporting, flushing, Custom Iterator etc. are all ok if this object is alive, and they will work together. If this object is destroyed, then no shared references to Processor, Exporter, *Recordable*, Custom Iterator etc. should exist, and all associated pipelines will have been flushed.

Public Functions

```

explicit TracerContext(std::vector<std::unique_ptr<SpanProcessor>> &&processor,
    opentelemetry::sdk::resource::Resource resource =
    opentelemetry::sdk::resource::Resource::Create({}), std::unique_ptr<Sampler>
    sampler = std::unique_ptr<AlwaysOnSampler>(new AlwaysOnSampler),
    std::unique_ptr<IdGenerator> id_generator = std::unique_ptr<IdGenerator>(new
    RandomIdGenerator())) noexcept

```

```

void AddProcessor(std::unique_ptr<SpanProcessor> processor) noexcept

```

Attaches a span processor to list of configured processors to this tracer context. Processor once attached can't be removed.

Note: This method is not thread safe.

Parameters **processor** – The new span processor for this tracer. This must not be a nullptr. Ownership is given to the *TracerContext*.

Sampler &**GetSampler()** const noexcept

Obtain the sampler associated with this tracer.

Returns The sampler for this tracer.

SpanProcessor &**GetProcessor()** const noexcept

Obtain the configured (composite) processor.

Note: When more than one processor is active, this will return an “aggregate” processor

const opentelemetry::sdk::resource::Resource &**GetResource()** const noexcept

Obtain the resource associated with this tracer context.

Returns The resource for this tracer context.

opentelemetry::sdk::trace::IdGenerator &**GetIdGenerator()** const noexcept

Obtain the Id Generator associated with this tracer context.

Returns The ID Generator for this tracer context.

bool **ForceFlush**(std::chrono::microseconds timeout = (std::chrono::microseconds::max)()) noexcept

Force all active SpanProcessors to flush any buffered spans within the given timeout.

bool **Shutdown**() noexcept

Shutdown the span processor associated with this tracer provider.

Class TracerProvider

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_tracer_provider.h`

Inheritance Relationships

Base Type

- public opentelemetry::trace::TracerProvider (*Class TracerProvider*)

Class Documentation

class **TracerProvider** : public opentelemetry::trace::TracerProvider

Public Functions

```
explicit TracerProvider(std::unique_ptr<SpanProcessor> processor,
                        opentelemetry::sdk::resource::Resource resource =
                        opentelemetry::sdk::resource::Resource::Create({}), std::unique_ptr<Sampler>
                        sampler = std::unique_ptr<AlwaysOnSampler>(new AlwaysOnSampler),
                        std::unique_ptr<opentelemetry::sdk::trace::IdGenerator> id_generator =
                        std::unique_ptr<opentelemetry::sdk::trace::IdGenerator>(new
                        RandomIdGenerator())) noexcept
```

Initialize a new tracer provider with a specified sampler

Parameters

- **processor** – The span processor for this tracer provider. This must not be a nullptr.
- **resource** – The resources for this tracer provider.
- **sampler** – The sampler for this tracer provider. This must not be a nullptr.
- **id_generator** – The custom id generator for this tracer provider. This must not be a nullptr

```
explicit TracerProvider(std::vector<std::unique_ptr<SpanProcessor>> &&processors,
                        opentelemetry::sdk::resource::Resource resource =
                        opentelemetry::sdk::resource::Resource::Create({}), std::unique_ptr<Sampler>
                        sampler = std::unique_ptr<AlwaysOnSampler>(new AlwaysOnSampler),
                        std::unique_ptr<opentelemetry::sdk::trace::IdGenerator> id_generator =
                        std::unique_ptr<opentelemetry::sdk::trace::IdGenerator>(new
                        RandomIdGenerator())) noexcept
```

```
explicit TracerProvider(std::shared_ptr<sdk::trace::TracerContext> context) noexcept
```

Initialize a new tracer provider with a specified context

Parameters context – The shared tracer configuration/pipeline for this provider.

```
~TracerProvider()
```

```
opentelemetry::nostd::shared_ptr<opentelemetry::trace::Tracer> GetTracer(nostd::string_view
                                                                    library_name,
                                                                    nostd::string_view
                                                                    library_version = "",
                                                                    nostd::string_view schema_url =
                                                                    "") noexcept override
```

```
void AddProcessor(std::unique_ptr<SpanProcessor> processor) noexcept
```

Attaches a span processor to list of configured processors for this tracer provider.

Note: This process may not receive any in-flight spans, but will get newly created spans. Note: This method is not thread safe, and should ideally be called from main thread.

Parameters processor – The new span processor for this tracer provider. This must not be a nullptr.

```
const opentelemetry::sdk::resource::Resource &GetResource() const noexcept
```

Obtain the resource associated with this tracer provider.

Returns The resource for this tracer provider.

bool **Shutdown**() noexcept

Shutdown the span processor associated with this tracer provider.

bool **ForceFlush**(std::chrono::microseconds timeout = (std::chrono::microseconds::max)()) noexcept

Force flush the span processor associated with this tracer provider.

Class DefaultSpan

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_default_span.h`

Inheritance Relationships

Base Type

- public opentelemetry::trace::Span (*Class Span*)

Class Documentation

class **DefaultSpan** : public opentelemetry::trace::Span

DefaultSpan provides a non-operational *Span* that propagates the tracer context by wrapping it inside the *Span* object.

Public Functions

inline virtual trace::SpanContext **GetContext**() const noexcept

inline virtual bool **IsRecording**() const noexcept

inline virtual void **SetAttribute**(nostd::string_view, const common::AttributeValue&) noexcept

inline virtual void **AddEvent**(nostd::string_view) noexcept

inline virtual void **AddEvent**(nostd::string_view, common::SystemTimestamp) noexcept

inline virtual void **AddEvent**(nostd::string_view, common::SystemTimestamp, const common::KeyValueIterable&) noexcept

inline virtual void **AddEvent**(nostd::string_view name, const common::KeyValueIterable &attributes) noexcept

inline virtual void **SetStatus**(StatusCode, nostd::string_view) noexcept

inline virtual void **UpdateName**(nostd::string_view) noexcept

inline virtual void **End**(const EndSpanOptions& = {}) noexcept

Mark the end of the *Span*. Only the timing of the first End call for a given *Span* will be recorded, and implementations are free to ignore all further calls.

Parameters *options* – can be used to manually define span properties like the end timestamp


```

inline nostd::string_view ToString() const noexcept

inline DefaultSpan(SpanContext span_context) noexcept

inline DefaultSpan(DefaultSpan &&spn) noexcept

inline DefaultSpan(const DefaultSpan &spn) noexcept

```

Public Static Functions

```

static inline DefaultSpan GetInvalid()

```

Class NoopSpan

- Defined in file `_home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_noop.h`

Inheritance Relationships

Base Type

- public `opentelemetry::trace::Span` (*Class Span*)

Class Documentation

class **NoopSpan** : public `opentelemetry::trace::Span`

No-op implementation of *Span*. This class should not be used directly.

Public Functions

```

inline explicit NoopSpan(const std::shared_ptr<Tracer> &tracer) noexcept

inline explicit NoopSpan(const std::shared_ptr<Tracer> &tracer, nostd::unique_ptr<SpanContext>
span_context) noexcept

inline virtual void SetAttribute(nostd::string_view, const common::AttributeValue&) noexcept override

inline virtual void AddEvent(nostd::string_view) noexcept override

inline virtual void AddEvent(nostd::string_view, common::SystemTimestamp) noexcept override

inline virtual void AddEvent(nostd::string_view, common::SystemTimestamp, const
common::KeyValueIterable&) noexcept override

inline virtual void SetStatus(StatusCode, nostd::string_view) noexcept override

inline virtual void UpdateName(nostd::string_view) noexcept override

```

inline virtual void **End**(const *EndSpanOptions*&) noexcept override

Mark the end of the *Span*. Only the timing of the first End call for a given *Span* will be recorded, and implementations are free to ignore all further calls.

Parameters *options* – can be used to manually define span properties like the end timestamp

inline virtual bool **IsRecording**() const noexcept override

inline virtual *SpanContext* **GetContext**() const noexcept override

Class NoopTracer

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_noop.h`

Inheritance Relationships

Base Types

- public opentelemetry::trace::Tracer (*Class Tracer*)
- public std::enable_shared_from_this< NoopTracer >

Class Documentation

class **NoopTracer** : public opentelemetry::trace::Tracer, public std::enable_shared_from_this<NoopTracer>

No-op implementation of *Tracer*.

Public Functions

inline virtual nostd::shared_ptr<*Span*> **StartSpan**(nostd::string_view, const common::KeyValueIterable&, const *SpanContextKeyValueIterable*&, const *StartSpanOptions*&) noexcept override

Starts a span.

Optionally sets attributes at *Span* creation from the given key/value pairs.

Attributes will be processed in order, previous attributes with the same key will be overwritten.

inline virtual void **ForceFlushWithMicroseconds**(uint64_t) noexcept override

inline virtual void **CloseWithMicroseconds**(uint64_t) noexcept override

Class NoopTracerProvider

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_noop.h`

Inheritance Relationships

Base Type

- public `opentelemetry::trace::TracerProvider` (*Class TracerProvider*)

Class Documentation

class **NoopTracerProvider** : public `opentelemetry::trace::TracerProvider`

No-op implementation of a *TracerProvider*.

Public Functions

inline **NoopTracerProvider**() noexcept

inline virtual `nostd::shared_ptr<opentelemetry::trace::Tracer>` **GetTracer**(`nostd::string_view` library_name,
`nostd::string_view` library_version,
`nostd::string_view` schema_url)
 noexcept override

Gets or creates a named tracer instance.

Optionally a version can be passed to create a named and versioned tracer instance.

Class NullSpanContext

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span_context_kv_iterable.h`

Inheritance Relationships

Base Type

- public `opentelemetry::trace::SpanContextKeyValueIterable` (*Class SpanContextKeyValueIterable*)

Class Documentation

class **NullSpanContext** : public opentelemetry::trace::SpanContextKeyValueIterable

Null *Span* context that does not carry any information.

Public Functions

inline virtual bool **ForEachKeyValue**(nostd::function_ref<bool(SpanContext, const opentelemetry::common::KeyValueIterable&>) const noexcept override

Iterate over SpanContext/key-value pairs

Parameters **callback** – a callback to invoke for each key-value for each SpanContext. If the callback returns false, the iteration is aborted.

Returns true if every SpanContext/key-value pair was iterated over

inline virtual size_t **size**() const noexcept override

Returns the number of key-value pairs

Class B3Propagator

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_b3_propagator.h

Inheritance Relationships

Base Type

- public opentelemetry::trace::propagation::B3PropagatorExtractor

Class Documentation

class **B3Propagator** : public opentelemetry::trace::propagation::B3PropagatorExtractor

Public Functions

inline void **Inject**(opentelemetry::context::propagation::TextMapCarrier &carrier, const context::Context &context) noexcept override

inline bool **Fields**(nostd::function_ref<bool(nostd::string_view)> callback) const noexcept override

Class B3PropagatorExtractor

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_b3_propagator.h`

Inheritance Relationships

Base Type

- public `opentelemetry::context::propagation::TextMapPropagator`

Derived Types

- public `opentelemetry::trace::propagation::B3Propagator` (*Class B3Propagator*)
- public `opentelemetry::trace::propagation::B3PropagatorMultiHeader` (*Class B3PropagatorMultiHeader*)

Class Documentation

class **B3PropagatorExtractor** : public `opentelemetry::context::propagation::TextMapPropagator`
 Subclassed by `opentelemetry::trace::propagation::B3Propagator`, `opentelemetry::trace::propagation::B3PropagatorMultiHeader`

Public Functions

inline `context::Context` **Extract**(const `opentelemetry::context::propagation::TextMapCarrier` &carrier, `context::Context` &context) noexcept override

Public Static Functions

static inline *TraceId* **TraceIdFromHex**(`nstd::string_view` trace_id)

static inline *SpanId* **SpanIdFromHex**(`nstd::string_view` span_id)

static inline *TraceFlags* **TraceFlagsFromHex**(`nstd::string_view` trace_flags)

Class B3PropagatorMultiHeader

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_b3_propagator.h`

Inheritance Relationships

Base Type

- public opentelemetry::trace::propagation::B3PropagatorExtractor

Class Documentation

class **B3PropagatorMultiHeader** : public opentelemetry::trace::propagation::B3PropagatorExtractor

Public Functions

inline void **Inject**(opentelemetry::context::propagation::TextMapCarrier &carrier, const context::Context &context) noexcept override

inline bool **Fields**(nostd::function_ref<bool(nostd::string_view)> callback) const noexcept override

Class HttpTraceContext

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_http_trace_context.h

Inheritance Relationships

Base Type

- public opentelemetry::context::propagation::TextMapPropagator

Class Documentation

class **HttpTraceContext** : public opentelemetry::context::propagation::TextMapPropagator

Public Functions

inline void **Inject**(opentelemetry::context::propagation::TextMapCarrier &carrier, const context::Context &context) noexcept override

inline context::Context **Extract**(const opentelemetry::context::propagation::TextMapCarrier &carrier, context::Context &context) noexcept override

Public Static Functions

static inline *TraceId* **TraceIdFromHex**(nstd::string_view trace_id)

static inline *SpanId* **SpanIdFromHex**(nstd::string_view span_id)

static inline *TraceFlags* **TraceFlagsFromHex**(nstd::string_view trace_flags)

Class JaegerPropagator

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_jaeger.h`

Inheritance Relationships

Base Type

- public `opentelemetry::context::propagation::TextMapPropagator`

Class Documentation

class **JaegerPropagator** : public `opentelemetry::context::propagation::TextMapPropagator`

Public Functions

inline void **Inject**(*context*::propagation::TextMapCarrier &carrier, const *context*::Context &context) noexcept override

inline *context*::Context **Extract**(const *context*::propagation::TextMapCarrier &carrier, *context*::Context &context) noexcept override

inline bool **Fields**(nstd::function_ref<bool(nstd::string_view)> callback) const noexcept override

Class Provider

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_provider.h`

Class Documentation

class **Provider**

Stores the singleton global *TracerProvider*.

Public Static Functions

static inline nostd::shared_ptr<*TracerProvider*> **GetTracerProvider**() noexcept

Returns the singleton *TracerProvider*.

By default, a no-op *TracerProvider* is returned. This will never return a nullptr *TracerProvider*.

static inline void **SetTracerProvider**(nostd::shared_ptr<*TracerProvider*> tp) noexcept

Changes the singleton *TracerProvider*.

Class Scope

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_scope.h`

Class Documentation

class **Scope**

Controls how long a span is active.

On creation of the *Scope* object, the given span is set to the currently active span. On destruction, the given span is ended and the previously active span will be the currently active span again.

Public Functions

inline **Scope**(const nostd::shared_ptr<*Span*> &span) noexcept

Initialize a new scope.

Parameters *span* – the given span will be set as the currently active span.

Class Span

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span.h`

Inheritance Relationships

Derived Types

- public `opentelemetry::trace::DefaultSpan` (*Class DefaultSpan*)
- public `opentelemetry::trace::NoopSpan` (*Class NoopSpan*)

Class Documentation

class **Span**

A *Span* represents a single operation within a Trace.

Subclassed by *opentelemetry::trace::DefaultSpan*, *opentelemetry::trace::NoopSpan*

Public Functions

Span() = default

virtual **~Span**() = default

Span(const *Span*&) = delete

Span(*Span*&&) = delete

Span &**operator**=(const *Span*&) = delete

Span &**operator**=(*Span*&&) = delete

virtual void **SetAttribute**(nostd::string_view key, const common::*AttributeValue* &value) noexcept = 0

virtual void **AddEvent**(nostd::string_view name) noexcept = 0

virtual void **AddEvent**(nostd::string_view name, common::*SystemTimestamp* timestamp) noexcept = 0

virtual void **AddEvent**(nostd::string_view name, common::*SystemTimestamp* timestamp, const common::*KeyValueIterable* &attributes) noexcept = 0

inline virtual void **AddEvent**(nostd::string_view name, const common::*KeyValueIterable* &attributes) noexcept

template<class **T**, nostd::enable_if_t<common::detail::is_key_value_iterable<*T*>::value>* = nullptr>

inline void **AddEvent**(nostd::string_view name, common::*SystemTimestamp* timestamp, const *T* &attributes) noexcept

template<class **T**, nostd::enable_if_t<common::detail::is_key_value_iterable<*T*>::value>* = nullptr>

inline void **AddEvent**(nostd::string_view name, const *T* &attributes) noexcept

inline void **AddEvent**(nostd::string_view name, common::*SystemTimestamp* timestamp, std::initializer_list<std::pair<nostd::string_view, common::*AttributeValue*>> attributes) noexcept

inline void **AddEvent**(nostd::string_view name, std::initializer_list<std::pair<nostd::string_view, common::*AttributeValue*>> attributes) noexcept

virtual void **SetStatus**(*StatusCode* code, nostd::string_view description = "") noexcept = 0

virtual void **UpdateName**(nostd::string_view name) noexcept = 0

virtual void **End**(const trace::*EndSpanOptions* &options = {}) noexcept = 0

Mark the end of the *Span*. Only the timing of the first End call for a given *Span* will be recorded, and implementations are free to ignore all further calls.

Parameters *options* – can be used to manually define span properties like the end timestamp

virtual trace::*SpanContext* **GetContext**() const noexcept = 0

virtual bool **IsRecording**() const noexcept = 0

Class SpanContext

- Defined in file `__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span_context.h`

Class Documentation

class **SpanContext**

Public Functions

inline **SpanContext**(bool sampled_flag, bool is_remote) noexcept

inline **SpanContext**(*TraceId* trace_id, *SpanId* span_id, *TraceFlags* trace_flags, bool is_remote, nstd::shared_ptr<*TraceState*> trace_state = *TraceState::GetDefault*()) noexcept

SpanContext(const *SpanContext* &ctx) = default

inline bool **IsValid**() const noexcept

inline const opentelemetry::trace::*TraceFlags* &**trace_flags**() const noexcept

inline const opentelemetry::trace::*TraceId* &**trace_id**() const noexcept

inline const opentelemetry::trace::*SpanId* &**span_id**() const noexcept

inline const nstd::shared_ptr<opentelemetry::trace::*TraceState*> **trace_state**() const noexcept

inline bool **operator==**(const *SpanContext* &that) const noexcept

SpanContext &**operator=**(const *SpanContext* &ctx) = default

inline bool **IsRemote**() const noexcept

inline bool **IsSampled**() const noexcept

Public Static Functions

static inline *SpanContext* **GetInvalid**() noexcept

Class `SpanContextKeyValueIterable`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span_context_kv_iterable.h`

Inheritance Relationships

Derived Type

- `public opentelemetry::trace::NullSpanContext` (*Class `NullSpanContext`*)

Class Documentation

class `SpanContextKeyValueIterable`

Supports internal iteration over a collection of `SpanContext`/key-value pairs.

Subclassed by *`opentelemetry::trace::NullSpanContext`*

Public Functions

virtual `~SpanContextKeyValueIterable()` = default

virtual bool **ForEachKeyValue**(`nostd::function_ref<bool(SpanContext, const opentelemetry::common::KeyValueIterable&)>` callback) const noexcept = 0

Iterate over `SpanContext`/key-value pairs

Parameters **callback** – a callback to invoke for each key-value for each `SpanContext`. If the callback returns false, the iteration is aborted.

Returns true if every `SpanContext`/key-value pair was iterated over

virtual `size_t` **size**() const noexcept = 0

Returns the number of key-value pairs

Class `SpanId`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span_id.h`

Class Documentation

class `SpanId`

Public Functions

```
inline SpanId() noexcept

inline explicit SpanId(nostd::span<const uint8_t, kSize> id) noexcept

inline void ToLowerBase16(nostd::span<char, 2 * kSize> buffer) const noexcept

inline nostd::span<const uint8_t, kSize> Id() const noexcept

inline bool operator==(const SpanId &that) const noexcept

inline bool operator!=(const SpanId &that) const noexcept

inline bool IsValid() const noexcept

inline void CopyBytesTo(nostd::span<uint8_t, kSize> dest) const noexcept
```

Public Static Attributes

```
static constexpr int kSize = 8
```

Class TraceFlags

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_trace_flags.h`

Class Documentation

class **TraceFlags**

Public Functions

```
inline TraceFlags() noexcept

inline explicit TraceFlags(uint8_t flags) noexcept

inline bool IsSampled() const noexcept

inline void ToLowerBase16(nostd::span<char, 2> buffer) const noexcept

inline uint8_t flags() const noexcept

inline bool operator==(const TraceFlags &that) const noexcept

inline bool operator!=(const TraceFlags &that) const noexcept

inline void CopyBytesTo(nostd::span<uint8_t, 1> dest) const noexcept
```

Public Static Attributes

```
static constexpr uint8_t kIsSampled = 1
```

Class TraceId

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_trace_id.h`

Class Documentation

class **TraceId**

Public Functions

```
inline TraceId() noexcept
```

```
inline explicit TraceId(nstd::span<const uint8_t, kSize> id) noexcept
```

```
inline void ToLowerBase16(nstd::span<char, 2 * kSize> buffer) const noexcept
```

```
inline nstd::span<const uint8_t, kSize> Id() const noexcept
```

```
inline bool operator==(const TraceId &that) const noexcept
```

```
inline bool operator!=(const TraceId &that) const noexcept
```

```
inline bool IsValid() const noexcept
```

```
inline void CopyBytesTo(nstd::span<uint8_t, kSize> dest) const noexcept
```

Public Static Attributes

```
static constexpr int kSize = 16
```

Class Tracer

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_tracer.h`

Inheritance Relationships

Derived Types

- public opentelemetry::sdk::trace::Tracer (*Class Tracer*)
- public opentelemetry::trace::NoopTracer (*Class NoopTracer*)

Class Documentation

class **Tracer**

Handles span creation and in-process context propagation.

This class provides methods for manipulating the context, creating spans, and controlling spans' lifecycles.

Subclassed by *opentelemetry::sdk::trace::Tracer*, *opentelemetry::trace::NoopTracer*

Public Functions

virtual **~Tracer**() = default

virtual nostd::shared_ptr<*Span*> **StartSpan**(nostd::string_view name, const common::KeyValueIterable &attributes, const *SpanContextKeyValueIterable* &links, const *StartSpanOptions* &options = {}) noexcept = 0

Starts a span.

Optionally sets attributes at *Span* creation from the given key/value pairs.

Attributes will be processed in order, previous attributes with the same key will be overwritten.

inline nostd::shared_ptr<*Span*> **StartSpan**(nostd::string_view name, const *StartSpanOptions* &options = {}) noexcept

template<class **T**, nostd::enable_if_t<common::detail::is_key_value_iterable<*T*>::value>* = nullptr>
inline nostd::shared_ptr<*Span*> **StartSpan**(nostd::string_view name, const *T* &attributes, const *StartSpanOptions* &options = {}) noexcept

inline nostd::shared_ptr<*Span*> **StartSpan**(nostd::string_view name, const common::KeyValueIterable &attributes, const *StartSpanOptions* &options = {}) noexcept

template<class **T**, class **U**, nostd::enable_if_t<common::detail::is_key_value_iterable<*T*>::value>* = nullptr,
nostd::enable_if_t<detail::is_span_context_kv_iterable<*U*>::value>* = nullptr>
inline nostd::shared_ptr<*Span*> **StartSpan**(nostd::string_view name, const *T* &attributes, const *U* &links,
const *StartSpanOptions* &options = {}) noexcept

inline nostd::shared_ptr<*Span*> **StartSpan**(nostd::string_view name,
std::initializer_list<std::pair<nostd::string_view,
common::AttributeValue>> attributes, const *StartSpanOptions*
&options = {}) noexcept

template<class **T**, nostd::enable_if_t<common::detail::is_key_value_iterable<*T*>::value>* = nullptr>

```
inline nostd::shared_ptr<Span> StartSpan(nostd::string_view name, const T &attributes,
                                         std::initializer_list<std::pair<SpanContext,
                                         std::initializer_list<std::pair<nostd::string_view,
                                         common::AttributeValue>>>> links, const StartSpanOptions
                                         &options = {}) noexcept
```

```
template<class T, nostd::enable_if_t<common::detail::is_key_value_iterable<T>::value>* = nullptr>
inline nostd::shared_ptr<Span> StartSpan(nostd::string_view name,
                                         std::initializer_list<std::pair<nostd::string_view,
                                         common::AttributeValue>> attributes, const T &links, const
                                         StartSpanOptions &options = {}) noexcept
```

```
inline nostd::shared_ptr<Span> StartSpan(nostd::string_view name,
                                         std::initializer_list<std::pair<nostd::string_view,
                                         common::AttributeValue>> attributes,
                                         std::initializer_list<std::pair<SpanContext,
                                         std::initializer_list<std::pair<nostd::string_view,
                                         common::AttributeValue>>>> links, const StartSpanOptions
                                         &options = {}) noexcept
```

```
template<class Rep, class Period>
inline void ForceFlush(std::chrono::duration<Rep, Period> timeout) noexcept
    Force any buffered spans to flush.
```

Parameters *timeout* – to complete the flush

```
virtual void ForceFlushWithMicroseconds(uint64_t timeout) noexcept = 0
```

```
template<class Rep, class Period>
inline void Close(std::chrono::duration<Rep, Period> timeout) noexcept
    ForceFlush any buffered spans and stop reporting spans.
```

Parameters *timeout* – to complete the flush

```
virtual void CloseWithMicroseconds(uint64_t timeout) noexcept = 0
```

Public Static Functions

```
static inline Scope WithActiveSpan(nostd::shared_ptr<Span> &span) noexcept
    Set the active span. The span will remain active until the returned Scope object is destroyed.
```

Parameters *span* – the span that should be set as the new active span.

Returns a *Scope* that controls how long the span will be active.

```
static inline nostd::shared_ptr<Span> GetCurrentSpan() noexcept
    Get the currently active span.
```

Returns the currently active span, or an invalid default span if no span is active.

Class TracerProvider

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_tracer_provider.h

Inheritance Relationships

Derived Types

- public opentelemetry::sdk::trace::TracerProvider (*Class TracerProvider*)
- public opentelemetry::trace::NoopTracerProvider (*Class NoopTracerProvider*)

Class Documentation

class TracerProvider

Creates new *Tracer* instances.

Subclassed by *opentelemetry::sdk::trace::TracerProvider*, *opentelemetry::trace::NoopTracerProvider*

Public Functions

virtual ~**TracerProvider**() = default

virtual nostd::shared_ptr<*Tracer*> **GetTracer**(nostd::string_view library_name, nostd::string_view library_version = "", nostd::string_view schema_url = "")
noexcept = 0

Gets or creates a named tracer instance.

Optionally a version can be passed to create a named and versioned tracer instance.

Class TraceState

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_trace_state.h

Class Documentation

class TraceState

TraceState carries tracing-system specific context in a list of key-value pairs. *TraceState* allows different vendors to propagate additional information and inter-operate with their legacy id formats.

For more information, see the W3C Trace Context specification: <https://www.w3.org/TR/trace-context>

Public Functions

inline std::string **ToHeader**() const noexcept

Creates a w3c tracestate header from *TraceState* object

inline bool **Get**(nostd::string_view key, std::string &value) const noexcept

Returns value associated with key passed as argument Returns empty string if key is invalid or not found

inline nostd::shared_ptr<*TraceState*> **Set**(const nostd::string_view &key, const nostd::string_view &value) noexcept

Returns shared_ptr of new *TraceState* object with following mutations applied to the existing instance:
Update Key value: The updated value must be moved to beginning of List Add : The new key-value pair SHOULD be added to beginning of List

If the provided key-value pair is invalid, or results in transtate that violates the tracecontext specification, empty *TraceState* instance will be returned.

If the existing object has maximum list members, it's copy is returned.

inline nostd::shared_ptr<*TraceState*> **Delete**(const nostd::string_view &key) noexcept

Returns shared_ptr to a new *TraceState* object after removing the attribute with given key (if present)

Returns empty *TraceState* object if key is invalid

Returns copy of original *TraceState* object if key is not present (??)

inline bool **Empty**() const noexcept

inline bool **GetAllEntries**(nostd::function_ref<bool(nostd::string_view, nostd::string_view)> callback) const noexcept

Public Static Functions

static inline nostd::shared_ptr<*TraceState*> **GetDefault**()

static inline nostd::shared_ptr<*TraceState*> **FromHeader**(nostd::string_view header) noexcept

Returns shared_ptr to a newly created *TraceState* parsed from the header provided.

Parameters header – Encoding of the tracestate header defined by the W3C Trace Context specification <https://www.w3.org/TR/trace-context/>

Returns *TraceState* A new *TraceState* instance or DEFAULT

static inline bool **IsValidKey**(nostd::string_view key)

Returns whether key is a valid key. See <https://www.w3.org/TR/trace-context/#key> Identifiers MUST begin with a lowercase letter or a digit, and can only contain lowercase letters (a-z), digits (0-9), underscores (_), dashes (-), asterisks (*), and forward slashes (/). For multi-tenant vendor scenarios, an at sign (@) can be used to prefix the vendor name.

static inline bool **IsValidValue**(nostd::string_view value)

Returns whether value is a valid value. See <https://www.w3.org/TR/trace-context/#value> The value is an opaque string containing up to 256 printable ASCII (RFC0020) characters ((i.e., the range 0x20 to 0x7E) except comma , and equal =)

Public Static Attributes

static constexpr int **kKeyMaxSize** = 256

static constexpr int **kValueMaxSize** = 256

static constexpr int **kMaxKeyValuePairs** = 32

static constexpr auto **kKeyValueSeparator** = '='

static constexpr auto **kMembersSeparator** = ','

3.1.3 Enums

Enum Decision

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_trace_sampler.h`

Enum Documentation

enum opentelemetry::sdk::trace::Decision

A sampling Decision for a Span to be created.

Values:

enumerator **DROP**

enumerator **RECORD_ONLY**

enumerator **RECORD_AND_SAMPLE**

Enum CanonicalCode

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_canonical_code.h`

Enum Documentation

enum opentelemetry::trace::CanonicalCode

Values:

enumerator **OK**

The operation completed successfully.

enumerator **CANCELLED**

The operation was cancelled (typically by the caller).

enumerator **UNKNOWN**

Unknown error. An example of where this error may be returned is if a Status value received from another address space belongs to an error-space that is not known in this address space. Also errors raised by APIs that do not return enough error information may be converted to this error.

enumerator **INVALID_ARGUMENT**

Client specified an invalid argument. Note that this differs from FAILED_PRECONDITION. INVALID_ARGUMENT indicates arguments that are problematic regardless of the state of the system (e.g., a malformed file name).

enumerator **DEADLINE_EXCEEDED**

Deadline expired before operation could complete. For operations that change the state of the system, this error may be returned even if the operation has completed successfully. For example, a successful response from a server could have been delayed long enough for the deadline to expire.

enumerator **NOT_FOUND**

Some requested entity (e.g., file or directory) was not found.

enumerator **ALREADY_EXISTS**

Some entity that we attempted to create (e.g., file or directory) already exists.

enumerator **PERMISSION_DENIED**

The caller does not have permission to execute the specified operation. PERMISSION_DENIED must not be used for rejections caused by exhausting some resource (use RESOURCE_EXHAUSTED instead for those errors). PERMISSION_DENIED must not be used if the caller cannot be identified (use UNAUTHENTICATED instead for those errors).

enumerator **RESOURCE_EXHAUSTED**

Some resource has been exhausted, perhaps a per-user quota, or perhaps the entire file system is out of space.

enumerator **FAILED_PRECONDITION**

Operation was rejected because the system is not in a state required for the operation's execution. For example, directory to be deleted may be non-empty, an rmdir operation is applied to a non-directory, etc.

A litmus test that may help a service implementor in deciding between FAILED_PRECONDITION, ABORTED, and UNAVAILABLE: (a) Use UNAVAILABLE if the client can retry just the failing call. (b)

Use **ABORTED** if the client should retry at a higher-level (e.g., restarting a read-modify-write sequence).
(c) Use **FAILED_PRECONDITION** if the client should not retry until the system state has been explicitly fixed. E.g., if an “**rmdir**” fails because the directory is non-empty, **FAILED_PRECONDITION** should be returned since the client should not retry unless they have first fixed up the directory by deleting files from it.

enumerator **ABORTED**

The operation was aborted, typically due to a concurrency issue like sequencer check failures, transaction aborts, etc.

See litmus test above for deciding between **FAILED_PRECONDITION**, **ABORTED**, and **UNAVAILABLE**.

enumerator **OUT_OF_RANGE**

Operation was attempted past the valid range. E.g., seeking or reading past end of file.

Unlike **INVALID_ARGUMENT**, this error indicates a problem that may be fixed if the system state changes. For example, a 32-bit file system will generate **INVALID_ARGUMENT** if asked to read at an offset that is not in the range $[0, 2^{32}-1]$, but it will generate **OUT_OF_RANGE** if asked to read from an offset past the current file size.

There is a fair bit of overlap between **FAILED_PRECONDITION** and **OUT_OF_RANGE**. We recommend using **OUT_OF_RANGE** (the more specific error) when it applies so that callers who are iterating through a space can easily look for an **OUT_OF_RANGE** error to detect when they are done.

enumerator **UNIMPLEMENTED**

Operation is not implemented or not supported/enabled in this service.

enumerator **INTERNAL**

Internal errors. Means some invariants expected by underlying system has been broken. If you see one of these errors, something is very broken.

enumerator **UNAVAILABLE**

The service is currently unavailable. This is a most likely a transient condition and may be corrected by retrying with a backoff.

See litmus test above for deciding between **FAILED_PRECONDITION**, **ABORTED**, and **UNAVAILABLE**.

enumerator **DATA_LOSS**

Unrecoverable data loss or corruption.

enumerator **UNAUTHENTICATED**

The request does not have valid authentication credentials for the operation.

Enum SpanKind

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span_metadata.h`

Enum Documentation

`enum opentelemetry::trace::SpanKind`

Values:

enumerator **kInternal**

enumerator **kServer**

enumerator **kClient**

enumerator **kProducer**

enumerator **kConsumer**

Enum StatusCode

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_span_metadata.h`

Enum Documentation

`enum opentelemetry::trace::StatusCode`

Values:

enumerator **kUnset**

enumerator **kOk**

enumerator **kError**

3.1.4 Functions

Function `opentelemetry::baggage::GetBaggage`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_baggage_baggage_context.h`

Function Documentation

```
inline nostd::shared_ptr<opentelemetry::baggage::Baggage> opentelemetry::baggage::GetBaggage(const
                                                                    open-
                                                                    teleme-
                                                                    try::context::Context
                                                                    &con-
                                                                    text)
                                                                    noexcept
```

Function `opentelemetry::baggage::SetBaggage`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_baggage_baggage_context.h`

Function Documentation

```
inline context::Context opentelemetry::baggage::SetBaggage(opentelemetry::context::Context &context,
                                                                    nostd::shared_ptr<opentelemetry::baggage::Baggage>
                                                                    baggage) noexcept
```

Function `opentelemetry::context::GetDefaultStorage`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_runtime_context.h`

Function Documentation

```
static RuntimeContextStorage *opentelemetry::context::GetDefaultStorage() noexcept
```

Construct and return the default *RuntimeContextStorage*

Returns a ThreadLocalContextStorage

Function `opentelemetry::sdk::resource::attr`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_resource_experimental_semantic_conventions.h`

Function Documentation

```
inline const char *opentelemetry::sdk::resource::attr(uint32_t attr)
```

Function `opentelemetry::trace::attr`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_experimental_semantic_conventions.h`

Function Documentation

```
inline const char *opentelemetry::trace::attr(uint32_t attr)
```

Function `opentelemetry::trace::GetSpan`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_context.h`

Function Documentation

```
inline nostd::shared_ptr<Span> opentelemetry::trace::GetSpan(const opentelemetry::context::Context
&context) noexcept
```

Function `opentelemetry::trace::propagation::detail::HexToBinary`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_detail_hex.h`

Function Documentation

```
inline bool opentelemetry::trace::propagation::detail::HexToBinary(nostd::string_view hex, uint8_t
*buffer, size_t buffer_size)
```

Converts a hexadecimal to binary format if the hex string will fit the buffer. Smaller hex strings are left padded with zeroes.

Function `opentelemetry::trace::propagation::detail::HexToInt`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_detail_hex.h`

Function Documentation

inline int8_t opentelemetry::trace::propagation::detail::HexToInt(char c)

Function `opentelemetry::trace::propagation::detail::IsValidHex`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_detail_hex.h`

Function Documentation

inline bool opentelemetry::trace::propagation::detail::IsValidHex(nostd::string_view s)

Function `opentelemetry::trace::propagation::detail::SplitString`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_detail_string.h`

Function Documentation

inline size_t opentelemetry::trace::propagation::detail::SplitString(nostd::string_view s, char separator, nostd::string_view *results, size_t count)

Splits a string by separator, up to given buffer count words. Returns the amount of words the input was split into.

Function `opentelemetry::trace::SetSpan`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_context.h`

Function Documentation

inline `context::Context` opentelemetry::trace::SetSpan(opentelemetry::context::Context &context, nostd::shared_ptr span) noexcept

3.1.5 Variables

Variable `opentelemetry::baggage::kBaggageHeader`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_baggage_baggage_context.h`

Variable Documentation

static const std::string opentelemetry::baggage::kBaggageHeader = "baggage"

Variable `opentelemetry::sdk::resource::attribute_ids`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_resource_experimental_semantic_conventions.h`

Variable Documentation

static const std::unordered_map<uint32_t, const char*> opentelemetry::sdk::resource::attribute_ids

Variable `opentelemetry::trace::attribute_id`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_experimental_semantic_conventions.h`

Variable Documentation

uint32_t opentelemetry::trace::attribute_id

Variable `opentelemetry::trace::attribute_ids`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_experimental_semantic_conventions.h`

Variable Documentation

static const struct opentelemetry::trace::[anonymous] opentelemetry::trace::attribute_ids[]

Stores the Constants for semantic kAttribute names outlined by the OpenTelemetry specifications. .

Variable Documentation

static const nstd::string_view opentelemetry::trace::propagation::kB3CombinedHeader = "b3"

Variable opentelemetry::trace::propagation::kB3SampledHeader

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_b3_propagator.h

Variable Documentation

static const nstd::string_view opentelemetry::trace::propagation::kB3SampledHeader = "X-B3-Sampled"

Variable opentelemetry::trace::propagation::kB3SpanIdHeader

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_b3_propagator.h

Variable Documentation

static const nstd::string_view opentelemetry::trace::propagation::kB3SpanIdHeader = "X-B3-SpanId"

Variable opentelemetry::trace::propagation::kB3TraceIdHeader

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_b3_propagator.h

Variable Documentation

static const nstd::string_view opentelemetry::trace::propagation::kB3TraceIdHeader = "X-B3-TraceId"

Variable opentelemetry::trace::propagation::kJaegerTraceHeader

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_jaeger.h

Variable Documentation

static const nstd::string_view opentelemetry::trace::propagation::kJaegerTraceHeader = "uber-trace-id"

Variable opentelemetry::trace::propagation::kSpanIdHexStrLength

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_b3_propagator.h

Variable Documentation

static const int opentelemetry::trace::propagation::kSpanIdHexStrLength = 16

Variable opentelemetry::trace::propagation::kSpanIdSize

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_http_trace_context.h

Variable Documentation

static const size_t opentelemetry::trace::propagation::kSpanIdSize = 16

Variable opentelemetry::trace::propagation::kTraceFlagsSize

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_http_trace_context.h

Variable Documentation

static const size_t opentelemetry::trace::propagation::kTraceFlagsSize = 2

Variable opentelemetry::trace::propagation::kTraceIdHexStrLength

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_b3_propagator.h

Variable Documentation

static const int opentelemetry::trace::propagation::kTraceIdHexStrLength = 32

Variable opentelemetry::trace::propagation::kTraceIdSize

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_http_trace_context.h

Variable Documentation

static const size_t opentelemetry::trace::propagation::kTraceIdSize = 32

Variable opentelemetry::trace::propagation::kTraceParent

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_http_trace_context.h

Variable Documentation

static const nstd::string_view opentelemetry::trace::propagation::kTraceParent = "traceparent"

Variable opentelemetry::trace::propagation::kTraceParentSize

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_http_trace_context.h

Variable Documentation

static const size_t opentelemetry::trace::propagation::kTraceParentSize = 55

Variable opentelemetry::trace::propagation::kTraceState

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_http_trace_context.h

Variable Documentation

static const nostd::string_view opentelemetry::trace::propagation::kTraceState = "tracestate"

Variable opentelemetry::trace::propagation::kVersionSize

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_propagation_http_trace_context.h

Variable Documentation

static const size_t opentelemetry::trace::propagation::kVersionSize = 2

3.1.6 Defines

Define HAVE_WORKING_REGEX

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_trace_state.h

Define Documentation

HAVE_WORKING_REGEX

Define OPENTELEMETRY_DEPRECATED

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_common_macros.h

Define Documentation

OPENTELEMETRY_DEPRECATED

Define OPENTELEMETRY_DEPRECATED_MESSAGE

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_common_macros.h

Define Documentation

OPENTELEMETRY_DEPRECATED_MESSAGE(msg)

Define OPENTELEMETRY_LIKELY_IF

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_common_macros.h

Define Documentation

OPENTELEMETRY_LIKELY_IF(...)

Define OPENTELEMETRY_MAYBE_UNUSED

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_common_macros.h

Define Documentation

OPENTELEMETRY_MAYBE_UNUSED

Declare variable as maybe unused usage: `OPENTELEMETRY_MAYBE_UNUSED int a; class OPENTELEMETRY_MAYBE_UNUSED a; OPENTELEMETRY_MAYBE_UNUSED int a();`.

Define OTEL_CPP_TRACE_ATTRIBUTES_MAX

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_experimental_semantic_conventions.h

Define Documentation

OTEL_CPP_TRACE_ATTRIBUTES_MAX

Define OTEL_GET_RESOURCE_ATTR

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_resource_experimental_semantic_conventions.h

Define Documentation

`OTEL_GET_RESOURCE_ATTR`(name)

Define `OTEL_GET_TRACE_ATTR`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_trace_experimental_semantic_conventions.h`

Define Documentation

`OTEL_GET_TRACE_ATTR`(name)

3.1.7 Typedefs

Typedef `opentelemetry::common::AttributeValue`

- Defined in `file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_common_attribute_value.h`

Typedef Documentation

`using opentelemetry::common::AttributeValue = nostd::variant<bool, int32_t, int64_t, uint32_t, double, const char*, nostd::string_view, nostd::span<const bool>, nostd::span<const int32_t>, nostd::span<const int64_t>, nostd::span<const uint32_t>, nostd::span<const double>, nostd::span<const nostd::string_view>, uint64_t, nostd::span<const uint64_t>, nostd::span<const uint8_t>>`

OpenTelemetry signals can be enriched by adding attributes. The `AttributeValue` type is defined as a variant of all attribute value types the OpenTelemetry C++ API supports.

The following attribute value types are supported by the OpenTelemetry specification:

- Primitive types: string, boolean, double precision floating point (IEEE 754-1985) or signed 64 bit integer.
- Homogenous arrays of primitive type values.

Warning:

The OpenTelemetry C++ API currently supports several attribute value types that are not covered by the OpenTelemetry specification:

- `uint64_t`
- `nostd::span<const uint64_t>`
- `nostd::span<uint8_t>`

Those types are reserved for future use and currently should not be used. There are no guarantees around how those values are handled by exporters.

Typedef opentelemetry::context::ContextValue

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_api_include_opentelemetry_context_context_value.h

Typedef Documentation

```
using opentelemetry::context::ContextValue = nostd::variant<nostd::monostate, bool, int64_t, uint64_t, double, nostd::shared_ptr<trace::Span>, nostd::shared_ptr<trace::SpanContext>, nostd::shared_ptr<baggage::Baggage>>
```

Typedef opentelemetry::sdk::resource::ResourceAttributes

- Defined in file__home_docs_checkouts_readthedocs.org_user_builds_opentelemetry-cpp_checkouts_v1.4.1_sdk_include_opentelemetry_sdk_resource_resource.h

Typedef Documentation

```
using opentelemetry::sdk::resource::ResourceAttributes = opentelemetry::sdk::common::AttributeMap
```


PERFORMANCE TESTS - BENCHMARKS

Click [here](#) to view the latest performance benchmarks for packages in this repo.

Please note that the fluctuation in the results are mainly because [machines with different CPUs](#) are used for tests.

GETTING HELP

- Refer to opentelemetry.io for general information about OpenTelemetry.
- Refer to the [OpenTelemetry C++ GitHub repository](#) for further information and resources related to OpenTelemetry C++.
- For questions related to OpenTelemetry C++ that are not covered by the existing documentation, please ask away in [GitHub discussions](#).
- Feel free to join the [CNCF OpenTelemetry C++ Slack channel](#). If you are new, you can create a CNCF Slack account [here](#).
- For bugs and feature requests, write a [GitHub issue](#).

INDEX

H

HAVE_WORKING_REGEX (*C macro*), 90

O

opentelemetry::baggage::Baggage (*C++ class*), 23

opentelemetry::baggage::Baggage::Baggage
(*C++ function*), 23

opentelemetry::baggage::Baggage::Delete
(*C++ function*), 23

opentelemetry::baggage::Baggage::FromHeader
(*C++ function*), 24

opentelemetry::baggage::Baggage::GetAllEntries
(*C++ function*), 23

opentelemetry::baggage::Baggage::GetDefault
(*C++ function*), 24

opentelemetry::baggage::Baggage::GetValue
(*C++ function*), 23

opentelemetry::baggage::Baggage::kKeyValueSeparator
(*C++ member*), 24

opentelemetry::baggage::Baggage::kMaxKeyValuePairs
(*C++ member*), 24

opentelemetry::baggage::Baggage::kMaxKeyValueSize
(*C++ member*), 24

opentelemetry::baggage::Baggage::kMaxSize
(*C++ member*), 24

opentelemetry::baggage::Baggage::kMembersSeparator
(*C++ member*), 24

opentelemetry::baggage::Baggage::kMetadataSeparator
(*C++ member*), 24

opentelemetry::baggage::Baggage::Set (*C++
function*), 23

opentelemetry::baggage::Baggage::ToHeader
(*C++ function*), 23

opentelemetry::baggage::GetBaggage (*C++ func-
tion*), 82

opentelemetry::baggage::kBaggageHeader (*C++
member*), 85

opentelemetry::baggage::propagation::BaggagePropagator
(*C++ class*), 24

opentelemetry::baggage::propagation::BaggagePropagator::Extract
(*C++ function*), 24

opentelemetry::baggage::propagation::BaggagePropagator::Fi
(*C++ function*), 24

opentelemetry::baggage::propagation::BaggagePropagator::Ir
(*C++ function*), 24

opentelemetry::baggage::SetBaggage (*C++ func-
tion*), 82

opentelemetry::common::AttributeValue (*C++
type*), 92

opentelemetry::common::KeyValueIterable
(*C++ class*), 25

opentelemetry::common::KeyValueIterable::~~KeyValueIterable
(*C++ function*), 25

opentelemetry::common::KeyValueIterable::ForEachKeyValue
(*C++ function*), 25

opentelemetry::common::KeyValueIterable::size
(*C++ function*), 25

opentelemetry::common::SteadyTimestamp (*C++
class*), 25

opentelemetry::common::SteadyTimestamp::operator
std::chrono::steady_clock::time_point
(*C++ function*), 26

opentelemetry::common::SteadyTimestamp::operator!=
(*C++ function*), 26

opentelemetry::common::SteadyTimestamp::operator==
(*C++ function*), 26

opentelemetry::common::SteadyTimestamp::SteadyTimestamp
(*C++ function*), 25

opentelemetry::common::SteadyTimestamp::time_since_epoch
(*C++ function*), 26

opentelemetry::common::SystemTimestamp (*C++
class*), 26

opentelemetry::common::SystemTimestamp::operator
std::chrono::system_clock::time_point
(*C++ function*), 26

opentelemetry::common::SystemTimestamp::operator!=
(*C++ function*), 27

opentelemetry::common::SystemTimestamp::operator==
(*C++ function*), 27

opentelemetry::common::SystemTimestamp::SystemTimestamp
(*C++ function*), 26

opentelemetry::common::SystemTimestamp::time_since_epoch
(*C++ function*), 27

opentelemetry::context::Context (C++ class), 27	(C++ function), 31
opentelemetry::context::Context::Context (C++ function), 27	opentelemetry::context::propagation::TextMapPropagator::Extract (C++ function), 31
opentelemetry::context::Context::GetValue (C++ function), 27	opentelemetry::context::propagation::TextMapPropagator::Fields (C++ function), 31
opentelemetry::context::Context::HasKey (C++ function), 27	opentelemetry::context::propagation::TextMapPropagator::Inject (C++ function), 31
opentelemetry::context::Context::operator== (C++ function), 27	opentelemetry::context::RuntimeContext (C++ class), 31
opentelemetry::context::Context::SetValue (C++ function), 27	opentelemetry::context::RuntimeContext::Attach (C++ function), 31
opentelemetry::context::Context::SetValues (C++ function), 27	opentelemetry::context::RuntimeContext::Detach (C++ function), 31
opentelemetry::context::ContextValue (C++ type), 93	opentelemetry::context::RuntimeContext::GetConstRuntimeContext (C++ function), 31
opentelemetry::context::GetDefaultStorage (C++ function), 82	opentelemetry::context::RuntimeContext::GetCurrent (C++ function), 31
opentelemetry::context::propagation::CompositePropagator (C++ class), 28	opentelemetry::context::RuntimeContext::GetValue (C++ function), 31
opentelemetry::context::propagation::CompositePropagator::CompositePropagator (C++ function), 28	opentelemetry::context::RuntimeContext::SetRuntimeContextStorage (C++ function), 31
opentelemetry::context::propagation::CompositePropagator::Extract (C++ function), 28	opentelemetry::context::RuntimeContext::SetValue (C++ function), 31
opentelemetry::context::propagation::CompositePropagator::Fields (C++ function), 28	opentelemetry::context::RuntimeContextStorage (C++ class), 32
opentelemetry::context::propagation::CompositePropagator::Inject (C++ function), 28	opentelemetry::context::RuntimeContextStorage::~RuntimeContextStorage (C++ function), 32
opentelemetry::context::propagation::GlobalTextMapPropagator (C++ class), 29	opentelemetry::context::RuntimeContextStorage::Attach (C++ function), 32
opentelemetry::context::propagation::GlobalTextMapPropagator::GetGlobalPropagator (C++ function), 29	opentelemetry::context::RuntimeContextStorage::CreateToken (C++ function), 33
opentelemetry::context::propagation::GlobalTextMapPropagator::SetGlobalPropagator (C++ function), 29	opentelemetry::context::RuntimeContextStorage::Detach (C++ function), 32
opentelemetry::context::propagation::NoOpPropagator (C++ class), 29	opentelemetry::context::RuntimeContextStorage::GetCurrent (C++ function), 32
opentelemetry::context::propagation::NoOpPropagator::Extract (C++ function), 29	opentelemetry::context::ThreadLocalContextStorage (C++ class), 33
opentelemetry::context::propagation::NoOpPropagator::Fields (C++ function), 29	opentelemetry::context::ThreadLocalContextStorage::Attach (C++ function), 33
opentelemetry::context::propagation::NoOpPropagator::Inject (C++ function), 29	opentelemetry::context::ThreadLocalContextStorage::Detach (C++ function), 33
opentelemetry::context::propagation::TextMapCarrier (C++ class), 30	opentelemetry::context::ThreadLocalContextStorage::GetCurrent (C++ function), 33
opentelemetry::context::propagation::TextMapCarrier::TextMapCarrier (C++ function), 30	opentelemetry::context::ThreadLocalContextStorage::ThreadLocalContextStorage (C++ function), 33
opentelemetry::context::propagation::TextMapCarrier::Keys (C++ function), 30	opentelemetry::context::Token (C++ class), 33
opentelemetry::context::propagation::TextMapCarrier::Set (C++ function), 30	opentelemetry::context::Token::~Token (C++ function), 34
opentelemetry::context::propagation::TextMapCarrier::Size (C++ function), 30	opentelemetry::context::Token::operator== (C++ function), 34
opentelemetry::context::propagation::TextMapPropagator (C++ class), 30	opentelemetry::sdk::instrumentationlibrary::InstrumentationLibrary (C++ class), 34
opentelemetry::context::propagation::TextMapPropagator::TextMapPropagator (C++ function), 30	opentelemetry::sdk::instrumentationlibrary::InstrumentationLibrary::InstrumentationLibrary (C++ function), 34

opentelemetry::sdk::instrumentationlibrary::InstrumentationLibraryTraceAllAlwaysOnSampler::ShouldSample
 (C++ function), 34
 opentelemetry::sdk::instrumentationlibrary::InstrumentationLibraryTraceAllBatchSpanProcessor
 (C++ function), 34
 opentelemetry::sdk::instrumentationlibrary::InstrumentationLibraryTraceAllBatchSpanProcessor::~BatchSpanProcessor
 (C++ function), 34
 opentelemetry::sdk::instrumentationlibrary::InstrumentationLibraryTraceAllBatchSpanProcessor::BatchSpanProcessor
 (C++ function), 34
 opentelemetry::sdk::instrumentationlibrary::InstrumentationLibraryTraceAllBatchSpanProcessor::ForceFlush
 (C++ function), 34
 opentelemetry::sdk::instrumentationlibrary::InstrumentationLibraryTraceAllBatchSpanProcessor::MakeRecordable
 (C++ function), 34
 opentelemetry::sdk::instrumentationlibrary::InstrumentationLibraryTraceAllBatchSpanProcessor::OnEnd
 (C++ function), 34
 opentelemetry::sdk::resource::attr (C++ function), 83
 opentelemetry::sdk::resource::attribute_ids (C++ member), 85
 opentelemetry::sdk::resource::OTELResourceDetector (C++ class), 35
 opentelemetry::sdk::resource::OTELResourceDetector::Detect (C++ function), 35
 opentelemetry::sdk::resource::Resource (C++ class), 36
 opentelemetry::sdk::resource::Resource::Create (C++ function), 36
 opentelemetry::sdk::resource::Resource::GetAttribute (C++ function), 36
 opentelemetry::sdk::resource::Resource::GetDefault (C++ function), 36
 opentelemetry::sdk::resource::Resource::GetEmpty (C++ function), 36
 opentelemetry::sdk::resource::Resource::GetSchemaURL (C++ function), 36
 opentelemetry::sdk::resource::Resource::Merge (C++ function), 36
 opentelemetry::sdk::resource::Resource::Resource (C++ function), 36
 opentelemetry::sdk::resource::ResourceAttributes (C++ type), 93
 opentelemetry::sdk::resource::ResourceDetector (C++ class), 37
 opentelemetry::sdk::resource::ResourceDetector::Detect (C++ function), 37
 opentelemetry::sdk::trace::AlwaysOffSampler (C++ class), 37
 opentelemetry::sdk::trace::AlwaysOffSampler::GetDescription (C++ function), 37
 opentelemetry::sdk::trace::AlwaysOffSampler::ShouldSample (C++ function), 37
 opentelemetry::sdk::trace::AlwaysOnSampler (C++ class), 38
 opentelemetry::sdk::trace::AlwaysOnSampler::GetDescription (C++ function), 38
 opentelemetry::sdk::trace::BatchSpanProcessor::OnStart (C++ function), 39
 opentelemetry::sdk::trace::BatchSpanProcessor::Shutdown (C++ function), 39
 opentelemetry::sdk::trace::BatchSpanProcessorOptions (C++ struct), 20
 opentelemetry::sdk::trace::BatchSpanProcessorOptions::max_batch_size (C++ member), 20
 opentelemetry::sdk::trace::BatchSpanProcessorOptions::max_queue_size (C++ member), 20
 opentelemetry::sdk::trace::BatchSpanProcessorOptions::schedule_delay (C++ member), 20
 opentelemetry::sdk::trace::Decision (C++ enum), 78
 opentelemetry::sdk::trace::Decision::DROP (C++ enumerator), 78
 opentelemetry::sdk::trace::Decision::RECORD_AND_SAMPLE (C++ enumerator), 78
 opentelemetry::sdk::trace::Decision::RECORD_ONLY (C++ enumerator), 78
 opentelemetry::sdk::trace::IdGenerator (C++ class), 40
 opentelemetry::sdk::trace::IdGenerator::~IdGenerator (C++ function), 40
 opentelemetry::sdk::trace::IdGenerator::GenerateSpanId (C++ function), 40
 opentelemetry::sdk::trace::IdGenerator::GenerateTraceId (C++ function), 40
 opentelemetry::sdk::trace::MultiRecordable (C++ class), 41
 opentelemetry::sdk::trace::MultiRecordable::AddEvent (C++ function), 41
 opentelemetry::sdk::trace::MultiRecordable::AddLink (C++ function), 41
 opentelemetry::sdk::trace::MultiRecordable::AddRecordable (C++ function), 41
 opentelemetry::sdk::trace::MultiRecordable::GetRecordable (C++ function), 41
 opentelemetry::sdk::trace::MultiRecordable::ReleaseRecordable (C++ function), 41

```

opentelemetry::sdk::trace::MultiRecordable::SetAttribute opentelemetry::sdk::trace::ParentBasedSampler::ShouldSample
  (C++ function), 41 (C++ function), 43
opentelemetry::sdk::trace::MultiRecordable::SetDescription opentelemetry::sdk::trace::RandomIdGenerator
  (C++ function), 41 (C++ class), 44
opentelemetry::sdk::trace::MultiRecordable::SetEvent opentelemetry::sdk::trace::RandomIdGenerator::GenerateSpan
  (C++ function), 41 (C++ function), 44
opentelemetry::sdk::trace::MultiRecordable::SetInstrumentationLibrary opentelemetry::sdk::trace::RandomIdGenerator::GenerateTrace
  (C++ function), 41 (C++ function), 44
opentelemetry::sdk::trace::MultiRecordable::SetName opentelemetry::sdk::trace::Recordable (C++
  (C++ function), 41 class), 44
opentelemetry::sdk::trace::MultiRecordable::SetResource opentelemetry::sdk::trace::Recordable::~~Recordable
  (C++ function), 41 (C++ function), 45
opentelemetry::sdk::trace::MultiRecordable::SetSpanKind opentelemetry::sdk::trace::Recordable::AddEvent
  (C++ function), 41 (C++ function), 45
opentelemetry::sdk::trace::MultiRecordable::SetStartTime opentelemetry::sdk::trace::Recordable::AddLink
  (C++ function), 41 (C++ function), 45
opentelemetry::sdk::trace::MultiRecordable::SetStatus opentelemetry::sdk::trace::Recordable::SetAttribute
  (C++ function), 41 (C++ function), 45
opentelemetry::sdk::trace::MultiSpanProcessor opentelemetry::sdk::trace::Recordable::SetDuration
  (C++ class), 42 (C++ function), 46
opentelemetry::sdk::trace::MultiSpanProcessor::opentelemetry::sdk::trace::Recordable::SetIdentity
  (C++ function), 43 (C++ function), 45
opentelemetry::sdk::trace::MultiSpanProcessor::AddProcessor opentelemetry::sdk::trace::Recordable::SetInstrumentationLibrary
  (C++ function), 42 (C++ function), 46
opentelemetry::sdk::trace::MultiSpanProcessor::ForceFlush opentelemetry::sdk::trace::Recordable::SetName
  (C++ function), 42 (C++ function), 46
opentelemetry::sdk::trace::MultiSpanProcessor::MakeRecording opentelemetry::sdk::trace::Recordable::SetResource
  (C++ function), 42 (C++ function), 46
opentelemetry::sdk::trace::MultiSpanProcessor::MultiSpanProcessor::trace::Recordable::SetSpanKind
  (C++ function), 42 (C++ function), 46
opentelemetry::sdk::trace::MultiSpanProcessor::OnEnd opentelemetry::sdk::trace::Recordable::SetStartTime
  (C++ function), 42 (C++ function), 46
opentelemetry::sdk::trace::MultiSpanProcessor::OnStart opentelemetry::sdk::trace::Recordable::SetStatus
  (C++ function), 42 (C++ function), 45
opentelemetry::sdk::trace::MultiSpanProcessor::ProcessorNode opentelemetry::sdk::trace::Sampler (C++
  (C++ struct), 21 class), 47
opentelemetry::sdk::trace::MultiSpanProcessor::ProcessorNode::next opentelemetry::sdk::trace::Sampler::~~Sampler
  (C++ member), 21 (C++ function), 47
opentelemetry::sdk::trace::MultiSpanProcessor::ProcessorNode::prev opentelemetry::sdk::trace::Sampler::GetDescription
  (C++ member), 21 (C++ function), 47
opentelemetry::sdk::trace::MultiSpanProcessor::ProcessorNode::ProcessorNode opentelemetry::sdk::trace::Sampler::ShouldSample
  (C++ function), 21 (C++ function), 47
opentelemetry::sdk::trace::MultiSpanProcessor::ProcessorNode::valuer opentelemetry::sdk::trace::SamplingResult
  (C++ member), 21 (C++ struct), 22
opentelemetry::sdk::trace::MultiSpanProcessor::Sampler opentelemetry::sdk::trace::SamplingResult::attributes
  (C++ function), 43 (C++ member), 22
opentelemetry::sdk::trace::MultiSpanProcessorOptions opentelemetry::sdk::trace::SamplingResult::decision
  (C++ struct), 21 (C++ member), 22
opentelemetry::sdk::trace::ParentBasedSampler opentelemetry::sdk::trace::SamplingResult::trace_state
  (C++ class), 43 (C++ member), 22
opentelemetry::sdk::trace::ParentBasedSampler::GetDescription opentelemetry::sdk::trace::SimpleSpanProcessor
  (C++ function), 43 (C++ class), 48
opentelemetry::sdk::trace::ParentBasedSampler::ParentBasedSampler opentelemetry::sdk::trace::SimpleSpanProcessor::~~SimpleSpanProcessor
  (C++ function), 43 (C++ function), 49

```

opentelemetry::sdk::trace::SimpleSpanProcessor::ForceFlush (C++ function), 48
 opentelemetry::sdk::trace::SimpleSpanProcessor::MakeRecordable (C++ function), 48
 opentelemetry::sdk::trace::SimpleSpanProcessor::OnEnd (C++ function), 48
 opentelemetry::sdk::trace::SimpleSpanProcessor::OnSetSpanData (C++ function), 48
 opentelemetry::sdk::trace::SimpleSpanProcessor::Shutdown (C++ function), 49
 opentelemetry::sdk::trace::SimpleSpanProcessor::SimpleSpanProcessor (C++ function), 48
 opentelemetry::sdk::trace::SpanData (C++ class), 49
 opentelemetry::sdk::trace::SpanData::AddEvent (C++ function), 51
 opentelemetry::sdk::trace::SpanData::AddLink (C++ function), 51
 opentelemetry::sdk::trace::SpanData::GetAttributes (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetDescription (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetDuration (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetEvents (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetInstrumentationLibrary (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetLinks (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetName (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetParentSpanId (C++ function), 49
 opentelemetry::sdk::trace::SpanData::GetResource (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetSpanContext (C++ function), 49
 opentelemetry::sdk::trace::SpanData::GetSpanId (C++ function), 49
 opentelemetry::sdk::trace::SpanData::GetSpanKind (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetStartTime (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetStatus (C++ function), 50
 opentelemetry::sdk::trace::SpanData::GetTraceId (C++ function), 49
 opentelemetry::sdk::trace::SpanData::SetAttributes (C++ function), 51
 opentelemetry::sdk::trace::SpanData::SetDuration (C++ function), 52
 opentelemetry::sdk::trace::SpanData::SetIdentity (C++ function), 50
 opentelemetry::sdk::trace::SpanData::SetInstrumentationLibrary (C++ function), 52
 opentelemetry::sdk::trace::SpanData::SetName (C++ function), 51
 opentelemetry::sdk::trace::SpanData::SetResource (C++ function), 52
 opentelemetry::sdk::trace::SpanData::SetSpanKind (C++ function), 51
 opentelemetry::sdk::trace::SpanData::SetStartTime (C++ function), 52
 opentelemetry::sdk::trace::SpanData::SetStatus (C++ function), 51
 opentelemetry::sdk::trace::SpanData::SpanData (C++ function), 49
 opentelemetry::sdk::trace::SpanDataEvent (C++ class), 52
 opentelemetry::sdk::trace::SpanDataEvent::GetAttributes (C++ function), 52
 opentelemetry::sdk::trace::SpanDataEvent::GetName (C++ function), 52
 opentelemetry::sdk::trace::SpanDataEvent::GetTimestamp (C++ function), 52
 opentelemetry::sdk::trace::SpanDataEvent::SpanDataEvent (C++ function), 52
 opentelemetry::sdk::trace::SpanDataLink (C++ class), 53
 opentelemetry::sdk::trace::SpanDataLink::GetAttributes (C++ function), 53
 opentelemetry::sdk::trace::SpanDataLink::GetSpanContext (C++ function), 53
 opentelemetry::sdk::trace::SpanDataLink::SpanDataLink (C++ function), 53
 opentelemetry::sdk::trace::SpanExporter (C++ class), 53
 opentelemetry::sdk::trace::SpanExporter::~SpanExporter (C++ function), 53
 opentelemetry::sdk::trace::SpanExporter::Export (C++ function), 53
 opentelemetry::sdk::trace::SpanExporter::MakeRecordable (C++ function), 53
 opentelemetry::sdk::trace::SpanExporter::Shutdown (C++ function), 54
 opentelemetry::sdk::trace::SpanProcessor (C++ class), 54
 opentelemetry::sdk::trace::SpanProcessor::~SpanProcessor (C++ function), 54
 opentelemetry::sdk::trace::SpanProcessor::ForceFlush (C++ function), 55
 opentelemetry::sdk::trace::SpanProcessor::MakeRecordable (C++ function), 54
 opentelemetry::sdk::trace::SpanProcessor::OnEnd (C++ function), 55
 opentelemetry::sdk::trace::SpanProcessor::OnStart (C++ function), 54

opentelemetry::sdk::trace::SpanProcessor::Shutdown	opentelemetry::sdk::trace::TracerProvider::ForceFlush
(C++ function), 55	(C++ function), 60
opentelemetry::sdk::trace::TraceIdRatioBasedSampler	opentelemetry::sdk::trace::TracerProvider::GetResource
(C++ class), 55	(C++ function), 59
opentelemetry::sdk::trace::TraceIdRatioBasedSampler::GetDescription	opentelemetry::sdk::trace::TracerProvider::GetTracer
(C++ function), 56	(C++ function), 59
opentelemetry::sdk::trace::TraceIdRatioBasedSampler::ShouldSample	opentelemetry::sdk::trace::TracerProvider::Shutdown
(C++ function), 56	(C++ function), 59
opentelemetry::sdk::trace::TraceIdRatioBasedSampler::TraceIdRatioBasedSampler	opentelemetry::sdk::trace::TracerProvider::TracerProvider
(C++ function), 56	(C++ function), 59
opentelemetry::sdk::trace::Tracer (C++ class), 56	opentelemetry::trace::attr (C++ function), 83
opentelemetry::sdk::trace::Tracer::CloseWithMicroseconds	opentelemetry::trace::attribute_id (C++ mem-
(C++ function), 57	bers), 85
opentelemetry::sdk::trace::Tracer::ForceFlushWithMicroseconds	opentelemetry::trace::attribute_ids (C++
(C++ function), 57	members), 85
opentelemetry::sdk::trace::Tracer::GetIdGenerator	opentelemetry::trace::attribute_key (C++
(C++ function), 57	member), 86
opentelemetry::sdk::trace::Tracer::GetInstrumentationLibrary	opentelemetry::trace::CanonicalCode (C++
(C++ function), 57	library), 79
opentelemetry::sdk::trace::Tracer::GetProcessor	opentelemetry::trace::CanonicalCode::ABORTED
(C++ function), 57	(C++ enumerator), 80
opentelemetry::sdk::trace::Tracer::GetResource	opentelemetry::trace::CanonicalCode::ALREADY_EXISTS
(C++ function), 57	(C++ enumerator), 79
opentelemetry::sdk::trace::Tracer::GetSampler	opentelemetry::trace::CanonicalCode::CANCELLED
(C++ function), 57	(C++ enumerator), 79
opentelemetry::sdk::trace::Tracer::StartSpan	opentelemetry::trace::CanonicalCode::DATA_LOSS
(C++ function), 56	(C++ enumerator), 80
opentelemetry::sdk::trace::Tracer::Tracer	opentelemetry::trace::CanonicalCode::DEADLINE_EXCEEDED
(C++ function), 56	(C++ enumerator), 79
opentelemetry::sdk::trace::TracerContext	opentelemetry::trace::CanonicalCode::FAILED_PRECONDITION
(C++ class), 57	(C++ enumerator), 79
opentelemetry::sdk::trace::TracerContext::AddProcessor	opentelemetry::trace::CanonicalCode::INTERNAL
(C++ function), 57	(C++ enumerator), 80
opentelemetry::sdk::trace::TracerContext::ForceFlush	opentelemetry::trace::CanonicalCode::INVALID_ARGUMENT
(C++ function), 58	(C++ enumerator), 79
opentelemetry::sdk::trace::TracerContext::GetIdGenerator	opentelemetry::trace::CanonicalCode::NOT_FOUND
(C++ function), 58	(C++ enumerator), 79
opentelemetry::sdk::trace::TracerContext::GetProcessor	opentelemetry::trace::CanonicalCode::OK
(C++ function), 58	(C++ enumerator), 79
opentelemetry::sdk::trace::TracerContext::GetResource	opentelemetry::trace::CanonicalCode::OUT_OF_RANGE
(C++ function), 58	(C++ enumerator), 80
opentelemetry::sdk::trace::TracerContext::GetSampler	opentelemetry::trace::CanonicalCode::PERMISSION_DENIED
(C++ function), 58	(C++ enumerator), 79
opentelemetry::sdk::trace::TracerContext::Shutdown	opentelemetry::trace::CanonicalCode::RESOURCE_EXHAUSTED
(C++ function), 58	(C++ enumerator), 79
opentelemetry::sdk::trace::TracerContext::TracerContext	opentelemetry::trace::CanonicalCode::UNAUTHENTICATED
(C++ function), 57	(C++ enumerator), 80
opentelemetry::sdk::trace::TracerProvider	opentelemetry::trace::CanonicalCode::UNAVAILABLE
(C++ class), 58	(C++ enumerator), 80
opentelemetry::sdk::trace::TracerProvider::~TracerProvider	opentelemetry::trace::CanonicalCode::UNIMPLEMENTED
(C++ function), 59	(C++ enumerator), 80
opentelemetry::sdk::trace::TracerProvider::AddProcessor	opentelemetry::trace::CanonicalCode::UNKNOWN
(C++ function), 59	(C++ enumerator), 79
	opentelemetry::trace::DefaultSpan (C++ class),

60

opentelemetry::trace::DefaultSpan::AddEvent (C++ function), 60

opentelemetry::trace::DefaultSpan::DefaultSpan (C++ function), 61

opentelemetry::trace::DefaultSpan::End (C++ function), 60

opentelemetry::trace::DefaultSpan::GetContext (C++ function), 60

opentelemetry::trace::DefaultSpan::GetInvalid (C++ function), 61

opentelemetry::trace::DefaultSpan::IsRecording (C++ function), 60

opentelemetry::trace::DefaultSpan::SetAttribute (C++ function), 60

opentelemetry::trace::DefaultSpan::SetStatus (C++ function), 60

opentelemetry::trace::DefaultSpan::ToString (C++ function), 60

opentelemetry::trace::DefaultSpan::UpdateName (C++ function), 60

opentelemetry::trace::EndSpanOptions (C++ struct), 22

opentelemetry::trace::EndSpanOptions::end_steadily (C++ member), 22

opentelemetry::trace::GetSpan (C++ function), 83

opentelemetry::trace::kSpanKey (C++ member), 86

opentelemetry::trace::NoopSpan (C++ class), 61

opentelemetry::trace::NoopSpan::AddEvent (C++ function), 61

opentelemetry::trace::NoopSpan::End (C++ function), 61

opentelemetry::trace::NoopSpan::GetContext (C++ function), 62

opentelemetry::trace::NoopSpan::IsRecording (C++ function), 62

opentelemetry::trace::NoopSpan::NoopSpan (C++ function), 61

opentelemetry::trace::NoopSpan::SetAttribute (C++ function), 61

opentelemetry::trace::NoopSpan::SetStatus (C++ function), 61

opentelemetry::trace::NoopSpan::UpdateName (C++ function), 61

opentelemetry::trace::NoopTracer (C++ class), 62

opentelemetry::trace::NoopTracer::CloseWithMicroseconds (C++ function), 62

opentelemetry::trace::NoopTracer::ForceFlushWithMicroseconds (C++ function), 62

opentelemetry::trace::NoopTracer::StartSpan (C++ function), 62

opentelemetry::trace::NoopTracerProvider (C++ class), 63

opentelemetry::trace::NoopTracerProvider::GetTracer (C++ function), 63

opentelemetry::trace::NoopTracerProvider::NoopTracerProvider (C++ function), 63

opentelemetry::trace::NullSpanContext (C++ class), 64

opentelemetry::trace::NullSpanContext::ForEachKeyValue (C++ function), 64

opentelemetry::trace::NullSpanContext::size (C++ function), 64

opentelemetry::trace::propagation::B3Propagator (C++ class), 64

opentelemetry::trace::propagation::B3Propagator::Fields (C++ function), 64

opentelemetry::trace::propagation::B3Propagator::Inject (C++ function), 64

opentelemetry::trace::propagation::B3PropagatorExtractor (C++ class), 65

opentelemetry::trace::propagation::B3PropagatorExtractor::Extract (C++ function), 65

opentelemetry::trace::propagation::B3PropagatorExtractor::Inject (C++ function), 65

opentelemetry::trace::propagation::B3PropagatorMultiHeader (C++ class), 66

opentelemetry::trace::propagation::B3PropagatorMultiHeader::Extract (C++ function), 66

opentelemetry::trace::propagation::B3PropagatorMultiHeader::Inject (C++ function), 66

opentelemetry::trace::propagation::detail::HexToBinary (C++ function), 83

opentelemetry::trace::propagation::detail::HexToInt (C++ function), 84

opentelemetry::trace::propagation::detail::IsValidHex (C++ function), 84

opentelemetry::trace::propagation::detail::kHexDigits (C++ member), 86

opentelemetry::trace::propagation::detail::SplitString (C++ function), 84

opentelemetry::trace::propagation::HttpTraceContext (C++ class), 66

opentelemetry::trace::propagation::HttpTraceContext::Extract (C++ function), 66

opentelemetry::trace::propagation::HttpTraceContext::Inject (C++ function), 66

opentelemetry::trace::propagation::HttpTraceContext::SpanId (C++ function), 67

opentelemetry::trace::propagation::HttpTraceContext::TraceId (C++ function), 67

opentelemetry::trace::propagation::HttpTraceContext::TraceState (C++ function), 67

(C++ function), 67	function), 69
opentelemetry::trace::propagation::JaegerPropagator (C++ class), 67	opentelemetry::trace::Span::IsRecording (C++ function), 70
opentelemetry::trace::propagation::JaegerPropagator::Extract (C++ function), 67	opentelemetry::trace::Span::operator= (C++ function), 69
opentelemetry::trace::propagation::JaegerPropagator::Fields (C++ function), 67	opentelemetry::trace::Span::SetAttribute (C++ function), 69
opentelemetry::trace::propagation::JaegerPropagator::Inject (C++ function), 67	opentelemetry::trace::Span::SetStatus (C++ function), 69
opentelemetry::trace::propagation::kB3CombinedHeader (C++ member), 87	opentelemetry::trace::Span::Span (C++ function), 69
opentelemetry::trace::propagation::kB3SampledHeader (C++ member), 87	opentelemetry::trace::Span::UpdateName (C++ function), 69
opentelemetry::trace::propagation::kB3SpanIdHeader (C++ member), 87	opentelemetry::trace::SpanContext (C++ class), 70
opentelemetry::trace::propagation::kB3TraceIdHeader (C++ member), 87	opentelemetry::trace::SpanContext::GetInvalid (C++ function), 70
opentelemetry::trace::propagation::kJaegerTraceIdHeader (C++ member), 88	opentelemetry::trace::SpanContext::IsRemote (C++ function), 70
opentelemetry::trace::propagation::kSpanIdHexSpanIdHeader (C++ member), 88	opentelemetry::trace::SpanContext::IsSampled (C++ function), 70
opentelemetry::trace::propagation::kSpanIdSize (C++ member), 88	opentelemetry::trace::SpanContext::IsValid (C++ function), 70
opentelemetry::trace::propagation::kTraceFlagsSize (C++ member), 88	opentelemetry::trace::SpanContext::operator= (C++ function), 70
opentelemetry::trace::propagation::kTraceIdHexSpanIdHeader (C++ member), 89	opentelemetry::trace::SpanContext::operator== (C++ function), 70
opentelemetry::trace::propagation::kTraceIdSize (C++ member), 89	opentelemetry::trace::SpanContext::span_id (C++ function), 70
opentelemetry::trace::propagation::kTraceParent (C++ member), 89	opentelemetry::trace::SpanContext::SpanContext (C++ function), 70
opentelemetry::trace::propagation::kTraceParentSize (C++ member), 89	opentelemetry::trace::SpanContext::trace_flags (C++ function), 70
opentelemetry::trace::propagation::kTraceState (C++ member), 90	opentelemetry::trace::SpanContext::trace_id (C++ function), 70
opentelemetry::trace::propagation::kVersionSize (C++ member), 90	opentelemetry::trace::SpanContext::trace_state (C++ function), 70
opentelemetry::trace::Provider (C++ class), 67	opentelemetry::trace::SpanContextKeyValueIterable (C++ class), 71
opentelemetry::trace::Provider::GetTracerProvider (C++ function), 68	opentelemetry::trace::SpanContextKeyValueIterable::~~SpanContextKeyValueIterable (C++ function), 71
opentelemetry::trace::Provider::SetTracerProvider (C++ function), 68	opentelemetry::trace::SpanContextKeyValueIterable::ForEach (C++ function), 71
opentelemetry::trace::Scope (C++ class), 68	opentelemetry::trace::SpanContextKeyValueIterable::size (C++ function), 71
opentelemetry::trace::Scope::Scope (C++ function), 68	opentelemetry::trace::SpanId (C++ class), 71
opentelemetry::trace::SetSpan (C++ function), 84	opentelemetry::trace::SpanId::CopyBytesTo (C++ function), 72
opentelemetry::trace::Span (C++ class), 69	opentelemetry::trace::SpanId::Id (C++ function), 72
opentelemetry::trace::Span::~~Span (C++ function), 69	opentelemetry::trace::SpanId::IsValid (C++ function), 72
opentelemetry::trace::Span::AddEvent (C++ function), 69	opentelemetry::trace::SpanId::kSize (C++ member), 72
opentelemetry::trace::Span::End (C++ function), 69	
opentelemetry::trace::Span::GetContext (C++	

`opentelemetry::trace::SpanId::operator!=` (C++ function), 72
`opentelemetry::trace::SpanId::operator==` (C++ function), 72
`opentelemetry::trace::SpanId::SpanId` (C++ function), 72
`opentelemetry::trace::SpanId::ToLowerBase16` (C++ function), 72
`opentelemetry::trace::SpanKind` (C++ enum), 81
`opentelemetry::trace::SpanKind::kClient` (C++ enumerator), 81
`opentelemetry::trace::SpanKind::kConsumer` (C++ enumerator), 81
`opentelemetry::trace::SpanKind::kInternal` (C++ enumerator), 81
`opentelemetry::trace::SpanKind::kProducer` (C++ enumerator), 81
`opentelemetry::trace::SpanKind::kServer` (C++ enumerator), 81
`opentelemetry::trace::StartSpanOptions` (C++ struct), 22
`opentelemetry::trace::StartSpanOptions::kind` (C++ member), 23
`opentelemetry::trace::StartSpanOptions::parent` (C++ member), 23
`opentelemetry::trace::StartSpanOptions::start_time` (C++ member), 23
`opentelemetry::trace::StartSpanOptions::start_time_system` (C++ member), 23
`opentelemetry::trace::StatusCode` (C++ enum), 81
`opentelemetry::trace::StatusCode::kError` (C++ enumerator), 81
`opentelemetry::trace::StatusCode::kOk` (C++ enumerator), 81
`opentelemetry::trace::StatusCode::kUnset` (C++ enumerator), 81
`opentelemetry::trace::TraceFlags` (C++ class), 72
`opentelemetry::trace::TraceFlags::CopyBytesTo` (C++ function), 72
`opentelemetry::trace::TraceFlags::flags` (C++ function), 72
`opentelemetry::trace::TraceFlags::IsSampled` (C++ function), 72
`opentelemetry::trace::TraceFlags::kIsSampled` (C++ member), 73
`opentelemetry::trace::TraceFlags::operator!=` (C++ function), 72
`opentelemetry::trace::TraceFlags::operator==` (C++ function), 72
`opentelemetry::trace::TraceFlags::ToLowerBase16` (C++ function), 72
`opentelemetry::trace::TraceFlags::TraceFlags` (C++ function), 72
`opentelemetry::trace::TraceId` (C++ class), 73
`opentelemetry::trace::TraceId::CopyBytesTo` (C++ function), 73
`opentelemetry::trace::TraceId::Id` (C++ function), 73
`opentelemetry::trace::TraceId::IsValid` (C++ function), 73
`opentelemetry::trace::TraceId::kSize` (C++ member), 73
`opentelemetry::trace::TraceId::operator!=` (C++ function), 73
`opentelemetry::trace::TraceId::operator==` (C++ function), 73
`opentelemetry::trace::TraceId::ToLowerBase16` (C++ function), 73
`opentelemetry::trace::TraceId::TraceId` (C++ function), 73
`opentelemetry::trace::Tracer` (C++ class), 74
`opentelemetry::trace::Tracer::~Tracer` (C++ function), 74
`opentelemetry::trace::Tracer::Close` (C++ function), 75
`opentelemetry::trace::Tracer::CloseWithMicroseconds` (C++ function), 75
`opentelemetry::trace::Tracer::ForceFlush` (C++ function), 75
`opentelemetry::trace::Tracer::ForceFlushWithMicroseconds` (C++ function), 75
`opentelemetry::trace::Tracer::GetCurrentSpan` (C++ function), 75
`opentelemetry::trace::Tracer::StartSpan` (C++ function), 74, 75
`opentelemetry::trace::Tracer::WithActiveSpan` (C++ function), 75
`opentelemetry::trace::TracerProvider` (C++ class), 76
`opentelemetry::trace::TracerProvider::~TracerProvider` (C++ function), 76
`opentelemetry::trace::TracerProvider::GetTracer` (C++ function), 76
`opentelemetry::trace::TraceState` (C++ class), 76
`opentelemetry::trace::TraceState::Delete` (C++ function), 77
`opentelemetry::trace::TraceState::Empty` (C++ function), 77
`opentelemetry::trace::TraceState::FromHeader` (C++ function), 77
`opentelemetry::trace::TraceState::Get` (C++ function), 77
`opentelemetry::trace::TraceState::GetAllEntries` (C++ function), 77
`opentelemetry::trace::TraceState::GetDefault`

(C++ *function*), [77](#)
opentelemetry::trace::TraceState::IsValidKey
(C++ *function*), [77](#)
opentelemetry::trace::TraceState::IsValidValue
(C++ *function*), [77](#)
opentelemetry::trace::TraceState::kKeyMaxSize
(C++ *member*), [78](#)
opentelemetry::trace::TraceState::kKeyValueSeparator
(C++ *member*), [78](#)
opentelemetry::trace::TraceState::kMaxKeyValuePairs
(C++ *member*), [78](#)
opentelemetry::trace::TraceState::kMembersSeparator
(C++ *member*), [78](#)
opentelemetry::trace::TraceState::kValueMaxSize
(C++ *member*), [78](#)
opentelemetry::trace::TraceState::Set (C++
function), [77](#)
opentelemetry::trace::TraceState::ToHeader
(C++ *function*), [77](#)
OPENTELEMETRY_DEPRECATED (C *macro*), [90](#)
OPENTELEMETRY_DEPRECATED_MESSAGE (C *macro*), [91](#)
OPENTELEMETRY_LIKELY_IF (C *macro*), [91](#)
OPENTELEMETRY_MAYBE_UNUSED (C *macro*), [91](#)
OTEL_CPP_TRACE_ATTRIBUTES_MAX (C *macro*), [91](#)
OTEL_GET_RESOURCE_ATTR (C *macro*), [92](#)
OTEL_GET_TRACE_ATTR (C *macro*), [92](#)